

First aid for external files and packages that need updating

Frank Mittelbach, L^AT_EX Project

2025/06/05

Abstract

This file contains some first aid for packages or classes that require updates because of internal changes to L^AT_EX but that aren't yet reflected in the package/class code.

Contents

| | | |
|----------|--|----------|
| 1 | Introduction | 2 |
| 1.1 | Minor kernel fixes | 2 |
| 2 | The Implementation | 2 |
| 2.1 | The filehook package first aid | 3 |
| 2.2 | The dinbrief class first aid | 5 |
| 2.3 | The unicode-math package first aid | 5 |
| 2.4 | The pgfpages and pgfmorepages first aid | 5 |
| 2.5 | The babel package | 6 |
| 2.6 | The songs package first aid | 6 |
| 2.7 | The crop package first aid | 6 |
| 2.8 | The bigfoot first aid | 7 |
| 2.9 | marginfix first aid | 7 |
| 2.10 | ulem first aid | 8 |
| 2.11 | varwidth first aid | 8 |
| 2.12 | The german class first aid | 9 |
| 2.13 | The underscore first aid | 9 |
| 2.14 | The acro package first aid | 10 |
| 2.15 | The chemformula package first aid | 10 |
| 2.16 | The chemnum package first aid | 10 |
| 2.17 | The cleveref package first aid | 10 |
| 2.18 | The arydshln package first aid | 12 |
| 2.19 | The calc package first aid | 13 |
| 2.20 | First aid after retiring the legacy mark mechanism | 13 |
| 2.21 | First aid for morewrites | 14 |

1 Introduction

Over the years package writers have hooked into various parts of internal L^AT_EX commands (largely because proper interfaces were missing in important places) and if we are now gradually adding such interfaces these internal commands do change and as a result patching into them stops working.

As part of making such internal changes the L^AT_EX Project team attempts to check for such usage in packages, alert the package maintainers and ensures that the packages get updated alongside the core L^AT_EX system. However it is not always possible to get packages that will fail with a new kernel updated in time and if that is the case we try to provide a temporary fix in this file for them. Once the package gets updated the fix will then be removed again.

For that reason, it is put into a separate bundle so that we can update it easily without requiring the CTAN maintainers to install a new full L^AT_EX system just because we take out (or add) a fix for a package here.

In the best case scenario the file documented here should be empty. In practice it will probably always contain one or the other fix while we are waiting for the package to get updated.

Important notice: The fixes provided here are not meant to be a permanent solution, but are only provided to support the transition period. They are (usually) neither complete nor necessarily the best solution! Furthermore, as they are done from the “outside”, they usually add some burden and slow down L^AT_EX processing, even if the package/class is not used in the document.

We will therefore remove such code as soon as possible again. In practice this means that if some package never gets updated/corrected, then it will eventually fail to work, because after one or at most two L^AT_EX releases we will take out the transition code to ensure that this “first aid patching” doesn’t get out of bounds.

1.1 Minor kernel fixes

If we encounter issues with the kernel code that should get fixed before the next main release we normally generate a patch release for L^AT_EX. However, depending on the complexity of the fix we might first add the fix here and generate a full patch release only when a number of such issues have accumulated. This way we lessen the impact on CTAN maintainers because for each tach release we have to make and distribute also a matching development release.

2 The Implementation

This file is meant to be loaded during format generation which is why we give it the extension .ltx.

```
1 {*kernel}
2 \def\LaTeXFirstAidDate{2025/06/05}
3 \def\LaTeXFirstAidVersion{v1.1p}
4 \ProvidesFile{latex2e-first-aid-for-external-files.ltx}
5           [\LaTeXFirstAidDate\space \LaTeXFirstAidVersion\space]
```

\FirstAidNeededT This is a very simple help to ensure that we only apply first aid to an unmodified package or class. It only works in the case the file has already been loaded and the csname \ver@#1.#2 got defined (holding the current date, version, and short description info). We then compare its content to a frozen string and make the modification #3 only if both agree. If they differ we assume that the package/class in question got updated by its maintainer.

```

7 \ExplSyntaxOn
8 \cs_new:Npn\FirstAidNeededT#1#2#3{
9   \exp_args:Nc\xstr_if_eq:onTF{ver@#1.#2}{#3}
10  { \typeout{==> First~ Aid~ for~ #1.#2~ applied! } }
11  { \typeout{==> First~ Aid~ for~ #1.#2~ no~ longer~ applied!^^J
12    @spaces Expected:^^J
13    @spaces@spaces #3^^J
14    @spaces but~ found:^^J
15    @spaces@spaces \use:c{ver@#1.#2}^^J
16    @spaces so~ I'm~ assuming~ it~ got~ fixed.
17  } }
18  \exp_args:Nc\xstr_if_eq:onT{ver@#1.#2}{#3}
19 }
20 \ExplSyntaxOff
21 </kernel>

```

2.1 The `filehook` package first aid

The `filehook` package implements hooks into file loading commands. These days this is already provided by the kernel albeit not with the same user interface. Until that package gets updated (to use the kernel interfaces) we provide a substitution. This does not offer all hooks from `filehook` but all that have been used in packages available in `TEX Live`.

Note that this doesn't fix `currfile` because that package uses `filehook` but relies on the internals of the old implementation.

The package has now got an update so we aren't activating the first aid. However, at the moment it basically bypasses the new hook mechanism and puts the old hooks in thereby disabling, for example, the possibility to re-order code through rules.

We therefore keep `filehook-ltx.sty` around as a guideline for further updates.

Replacing `filehook` with a leaner version would then work like this:

```

22 <*kernel>
23 %\declare@file@substitution{filehook.sty}{filehook-ltx.sty}
24 </kernel>

```

What follows is a simplified (partial) implementation of the `filehook` interfaces. Not implemented are:

```

\AtBeginOfFiles      \AtEndOfFiles
\AtBeginOfInputs     \AtEndOfInputs
\AtBeginOfInputFile  \AtEndOfInputFile

```

```
25 <*filehook-ltx>
```

```

26 \newcommand\AtBeginOfEveryFile [1]
27   {\AddToHook{file/before}{#1}}
28 \newcommand\AtEndOfEveryFile [1]
29   {\AddToHook{file/after}{#1}}
30 \newcommand\AtBeginOfIncludes [1]
31   {\AddToHook{include/before}{#1}}
32 \newcommand\AtEndOfIncludes [1]
33   {\AddToHook{include/end}{#1}}
34 \newcommand\AfterIncludes [1]
35   {\AddToHook{include/after}{#1}}
36 \newcommand\AtBeginOfPackages [1]
37   {\AddToHook{package/before}{#1}}
38 \newcommand\AtEndOfPackages [1]
39   {\AddToHook{package/after}{#1}}
40 \newcommand\AtBeginOfClasses [1]
41   {\AddToHook{class/before}{#1}}
42 \newcommand\AtEndOfClasses [1]
43   {\AddToHook{class/after}{#1}}
44 \newcommand\AtBeginOfFile [2]
45   {\AddToHook{file/#1/before}{#2}}
46 \newcommand\AtEndOfFile [2]
47   {\AddToHook{file/#1/after}{#2}}

```

Some commands offered a starred form

```

48 \DeclareDocumentCommand \AtBeginOfPackageFile {smm}
49   {\IfBooleanTF{#1}%
50     {\@ifpackageloaded{#2}%
51      {#3}%
52      {\AddToHook{package/#2/before}{#3}}}}%
53   {\AddToHook{package/#2/before}{#3}}%
54 }
55 \DeclareDocumentCommand \AtEndOfPackageFile {smm}
56   {\IfBooleanTF{#1}%
57     {\@ifpackageloaded{#2}%
58      {#3}%
59      {\AddToHook{package/#2/after}{#3}}}}%
60   {\AddToHook{package/#2/after}{#3}}%
61 }

```

Are the * forms here of any use? I know they are used 3–4 times on CTAN but I wonder if those are real or mistaken usages.

```

62 \DeclareDocumentCommand \AtBeginOfClassFile {smm}
63   {\IfBooleanTF{#1}%
64     {\@ifclassloaded{#2}%
65      {#3}%
66      {\AddToHook{class/#2/before}{#3}}}}%
67   {\AddToHook{class/#2/before}{#3}}%
68 }
69 \DeclareDocumentCommand \AtEndOfClassFile {smm}
70   {\IfBooleanTF{#1}%
71     {\@ifclassloaded{#2}%
72      {#3}}}

```

```

73      {\AddToHook{class/#2/after}{#3}}}%
74      {\AddToHook{class/#2/after}{#3}}%
75  }
76 \newcommand\AtBeginOfIncludeFile [2]
77  {\AddToHook{include/#1/before}{#2}}
78 \newcommand\AtEndOfIncludeFile [2]
79  {\AddToHook{include/#1/end}{#2}}
80 \newcommand\AfterIncludeFile [2]
81  {\AddToHook{include/#1/after}{#2}}
82 {/filehook-ltx}
83 (*kernel)

```

2.2 The **dinbrief** class first aid

Again a case of a no longer correct `\endgroup` in document. Here the fix is simply though.

```

84 \AddToHook{file/dinbrief.cls/after}[firstaid]{%
85   \FirstAidNeededT{dinbrief}{cls}{2000/03/02 LaTeXe class}%
86           {\AddToHook{env/document/begin}{\begingroup}}%
87 }

```

2.3 The **unicode-math** package first aid

If `unicode-math` is used together with `doc` there is a problem because it changes the mathcodes without adjusting the use in `doc` that assume standard settings. Could be fixed on either side, but as `unicode-math` is derivating from the standard, the right place is probably a fix in this package. For now we do it here. See [github/820](#).

```

88 \AddToHook{package/unicode-math/after}{%
89   \AddToHook{cmd/mod@math@codes/after}{\mathcode`\\|=28796 }}

```

2.4 The **pgfpages** and **pgfmorepages** first aid

`pgfpages` alters the `\shipout` primitive to support multiple page up scenarios. If used together with `atbegshi` that worked because the alterations done by `atbegshi` came later and so used the new definition provide by `pgfpages`. Now that the code from `atbegshi` is already in the kernel this further redefinition doesn't happen with the result that the change to `\shipout` comes to late and breaks the kernel processes.

```

90 \ExplSyntaxOn
91 \AddToHook{file/pgfpages.sty/after}[firstaid]{%

```

Undo overwriting `\shipout`:

```

92   \cs_gset_eq:NN \shipout \pgfpages@originalshipout

```

Instead overwrite the L3 programming layer name of the primitive. This is really an absolute no-go, but for now the simplest solution to keep the original code running.

It will be replaced when the “configuration points” interface for L^AT_EX becomes available. At that point the package will be able to set up a different strategy for doing shipouts and without the need to overwrite a primitive (which it did in the past and which we do below) and then this code here can be taken out again.

```

93  \cs_set_eq:NN \pgfpages@originalshipout \tex_shipout:D
94  \cs_set_eq:NN \tex_shipout:D \pgfpages@interceptshipout
95 }
96 \ExplSyntaxOff

Same issue with pgfmorepages but slightly different implementation (sigh).

97 \ExplSyntaxOn
98 \AddToHook{file/pgfmorepages.sty/after}[firstaid]{
99   \cs_set_nopar:Npn \pgfhookintoshipout {
100     \cs_set_eq:NN \pgfpages@originalshipout \tex_shipout:D
101     \cs_set_eq:NN \tex_shipout:D \pgfpages@interceptshipout
102   }
103 }
104 \ExplSyntaxOff

```

2.5 The **babel** package

Turn off the **babel** hack.

```
105 \AddToHook{file/babel.sty/before}[firstaid]{\def\BabelCaseHack{}}
```

2.6 The **songs** package first aid

The songs package uses `\obeylines` and redefines `\par` for special effect. this no longer works in L^AT_EX 2022-06-01 (gh issue 367). The following fixes at least one failure.

```

106 \AddToHook{file/songs.sty/after}[firstaid]{%
107   \FirstAidNeededT{songs}{sty}{2018/09/12 v3.1 Songs package}%
108   {%
109     \renewcommand\SB@obeylines{%
110       \let\obeyedline\SB@par%
111       \obeylines%
112       \let\@par\SB@@par%
113     }%
114 }

```

2.7 The **crop** package first aid

The crop packages fails currently due to two L^AT_EX changes: It doesn't know that `\stockheight` and `\stockwidth` are now defined, and doesn't take into account that `\rlap` is robust (<https://github.com/rrthomas/crop/issues/2>). The first is addressed by setting the dimension if they are zero or negative. For the second we locally change the meaning of `\protect`

```

115 \AddToHook{file/crop.sty/after}[firstaid]{%
116   \FirstAidNeededT{crop}{sty}{2017/11/19 1.10 crop marks (mf)}%
117   {%
118     \ifdim\stockwidth > 0pt \else \stockwidth\paperwidth \fi
119     \ifdim\stockheight > 0pt \else \stockheight\paperheight \fi
120     \renewcommand*\CROP@genreflect[1]{%
121       \leavevmode
122       \dimen0\cROP@horigin
123       \kern2\dimen0
124       \begingroup

```

```

125  \set@typeset@protect %change protect
126  \reflectbox{%
127      \hb@xt@\paperwidth{%
128          \vbox to\paperheight{%
129              #1%
130              \vss
131          }%
132      \hss
133      }%
134  }%
135  \endgroup
136  }
137 }%
138 }

```

2.8 The **bigfoot** first aid

The **bigfoot** packages makes the assumption that two `\newinsert` allocations have a recognisable order in their numbers, the second one has a lower number. This was correct in the classic **TEX** implementation but with the extended allocation possibilities of all modern engines is no longer the case and there is a point where the allocations take a “jump” breaking the ordering assumption. These days we are fairly close to that point and depending on how many packages are loaded before **bigfoot** the package breaks.

This `firstaid` therefore jumps over the problematical point by pushing the count allocation to a safe value if necessary.

```

139 \AddToHook{file/bigfoot.sty/after}{%
140     \ifnum\count10<\insc@unt
141         \global\count10=\insc@unt
142     \fi

```

We also correct a bug that **bigfoot** tries to shift mark registers, but in **LATEX** (at least since 2015) the allocation number is not 266, so it does that to a random number of mark registers (which sometimes blows up depending on the value in 266).

```

143     \def\FN@allmarks#1{\@elt{#1}%
144         \ifnum#1<\count256 %<--- problem: 266 isn't the counter for marks
145             \expandafter\FN@allmarks\expandafter{\number\numexpr#1+1\@ne}%
146         \fi}%
147 }

```

2.9 **marginfix** first aid

The **marginfix** package tries to patch `\@combinefloats` but with 2025-06 the kernel doesn’t use this any longer but uses `\@outputbox@attachfloats` instead.

```

148 \AddToHook{file/marginfix.sty/after}[firstaid]{%
149     \FirstAidNeededT{marginfix}{sty}%
150     {2020/05/06 v1.2 Fix Margin Paragraphs}%
151     {\let \@outputbox@attachfloats \@combinefloats}%
152 }

```

2.10 **ulem** first aid

In 2020 we fixed various kernel commands to accept `calc` syntax. The `ulem` package redefines some internals and that now conflicts with the new definitions as they involve an extra group. So we alter the definition of `\@hskip` if `ulem` was loaded. This is not perfect, obviously, so it will go out the moment `ulem` gets adjusted.

```
153 \AddToHook{file/ulem.sty/after}[firstaid]{%
154   \def\@hskip{\begingroup\setlength\skip@{#1}%
155           \edef\x{\endgroup\hskip\the\skip@\relax}\x}%
156 }
```

2.11 **varwidth** first aid

The `varwidth` package does a lot of low-level paragraph manipulation assuming traditional TeX paragraphs. However, with the paragraph hooks we end up with one extra glue `0pt` item on the vertical list and if that isn't removed then the package doesn't find its penalties.

So this needs to be removed as well by adding an additional `\unskip`.

```
157 \AddToHook{file/varwidth.sty/after}[firstaid]{%
158   \FirstAidNeededT{varwidth}{sty}%
159   {2009/03/30 ver 0.92; \space Variable-width minipages}%
160   {%
161     \def\@vwid@sift{%
162       \skip@\lastskip\unskip
163       \ifdim\lastskip=\z@\unskip\fi    % ----- the first aid here (not just unskip)
164       \dimen@\lastkern\unkern
165       \count@\lastpenalty\unpenalty
166       \setbox\z@\lastbox
167       \ifvoid\z@\advance\sift@deathcycles@one \else \sift@deathcycles\z@\fi
168       \ifnum\sift@deathcycles>33
169         \let\@vwid@sift\relax
170         \PackageWarning{varwidth}{Failed to reprocess entire contents}%
171       \fi
172       \ifnum\count@=\@vwid@preeqp \@vwid@eqmodefalse\fi
173       \ifnum\count@=\@vwid@posteqp \@vwid@eqmodetrue\fi
174       \ifnum\count@=\@vwid@toppen % finished
175         \let\@vwid@sift\relax
176       \else\ifnum\count@=\@vwid@offsets
177         \@vwid@setoffsets
178       \else
179         \ifnum\count@=\@vwid@postw
180           \else
181             \@vwid@resetb % reset box \z@ or measure it
182           \fi
183           \@vwid@append
184         \fi\fi
185       \@vwid@sift}%
186     }%
187   }
```

2.12 The **german** class first aid

Handling of \protected UTF-8

```
188 \AddToHook{file/german.sty/after}[firstaid]{%
189   \FirstAidNeededT{german}{sty}{1998/07/08 v2.5e Support for writing german texts (br)}{%
190   }%
191 \let\grmn@active@dq@\@active@dq
192 \def@\active@dq{\protect\grmn@active@dq}%
193 \germanTeX
194 }%
195 }

196 \AddToHook{file/ngerman.sty/after}[firstaid]{%
197   \FirstAidNeededT{ngerman}{sty}{1998/07/08 v2.5e Support for writing german texts (br)}{%
198   }%
199 \let\grmn@active@dq@\@active@dq
200 \def@\active@dq{\protect\grmn@active@dq}%
201 \ngermanTeX
202 }%
203 }

204 </kernel>
```

2.13 The **underscore** first aid

The **underscore** package makes the underscore active. This means that the underscore can not be used in label and references unless the package option **strings** is used (which patches a selection of problematic commands like `\label` and `\ref`) or **babel** is used which redefines¹ a selection of problematic commands like `\@testdef` or `\@newl@bel`.

With the new property commands the work-around do not work. We therefore make the underscore protected and use `\ifinclsname` to allow its use in csnames.

```
205 <*underscore-ltx>
206 \ProvidesPackage{underscore-ltx}[2023/09/20 LaTeX firstaid to make underscore protected ]
207 \begingroup
208 \catcode`\_=active
209 \protected\gdef _{%
210   \ifinclsname %
211     \string_%
212   \else
213     \ifx\protect\@typeset@protect
214       \ifmmode \sb \else \BreakableUnderscore \fi
215     \else
216       \ifx\protect\@unexpandable@protect \noexpand_%
217         \else \protect_%
218       \fi\fi
219     \fi
220   }
221 \global\let\ActiveUnderscore=_
222 \endgroup
223 </underscore-ltx>
```

¹unless the recommended option `safe=none` is used

```

224 <*kernel>
225 \AddToHook{file/underscore.sty/after}[firstaid]{%
226   \FirstAidNeededT{underscore}{sty}{2006/09/13}{\RequirePackage{underscore-ltx}}}
227 </kernel>
228 <*kernel>

```

2.14 The **acro** package first aid

The package does not declare a `prop`, which causes an issue with newer routines in `expl3`.

```

229 \AddToHook{package/acro/after}[firstaid]{%
230   \FirstAidNeededT{acro}{sty}{2022/04/01 v3.8 typeset acronyms
231     and other abbreviations (CN)}
232   {\UseName{prop_new:c}{l__acro_tmpa_prop}}%

```

With the 2024 June release of L^AT_EX it will also fail to patch `\endlongtable` and therefore errors when loading. However, the patch it tries never worked (because it was setting a local boolean at a point where it was more or less immediately reset). Thus, rather than fixing the patch approach (which requires to surround the patch with `\ExplSyntaxOn \catcode`_ = 10 \ExplSyntaxOff`) we simply disable the patch for now.

```

233   \acsetup{patch/longtable=false}%
234 }%
235 }

```

2.15 The **chemformula** package first aid

Package `chemformula` uses `l3keys2e` for option processing. This used to be made available as `chemformula` also loads `xfrac`, which loaded `l3keys2e`. However, `xfrac` has now been updated to use the newer kernel method if available, so loading `chemformula` fails.

```

236 \AddToHook{package/chemformula/before}[firstaid]{%
237   \RequirePackage{l3keys2e}}%
238 }

```

2.16 The **chemnum** package first aid

The package does not declare a `prop`, which causes an issue with newer routines in `expl3`.

```

239 \AddToHook{package/chemnum/after}[firstaid]{%
240   \FirstAidNeededT{chemnum}{sty}{2021/01/21 v1.3a a comprehensive
241     approach for the numbering of chemical compounds (CN)}
242   {\UseName{prop_new:c}{l__chemnum_tmpa_prop}}%
243 }

```

2.17 The **cleveref** package first aid

The `cleveref` package expects only two data containers for its internal `\newlabel` command. This fails if `xr-hyper` is used which expands every `\newlabel` to five data container and puts the file name into the last one.

```

244 \AddToHook{package/cleveref/after}[firstaid]{%

```

```

245 \FirstAidNeededT{cleveref}{sty}{2018/03/27 v0.21.4 Intelligent cross-referencing}
246   {%

```

This are the two commands which retrieve the data from the label info. We change them to expect five arguments.

```

247   \def\cref@getref#1#2{%
248     \expandafter\let\expandafter#2\csname r@#1@cref\endcsname%
249     \expandafter\expandafter\expandafter\def%
250       \expandafter\expandafter\expandafter#2%
251       \expandafter\expandafter\expandafter{%
252         \expandafter\@firstoffive#2}%
253   }% <----- five
254   \def\cpageref@getref#1#2{%
255     \expandafter\let\expandafter#2\csname r@#1@cref\endcsname%
256     \expandafter\expandafter\expandafter\def%
257       \expandafter\expandafter\expandafter#2%
258       \expandafter\expandafter\expandafter{%
259         \expandafter\@secondoffive#2}%
260   }% <----- five

```

We also need to redefine the internal label commands of cleveref. This must be done after cleveref has made its changes in begindocument so we add it to the same hook using the hook label used by cleveref. This way it is guaranteed to overwrite the definitions.

```

261   \AddToHook{begindocument}[cleveref]{%
262     \def\label@noarg#1{%
263       \cref@old@label{#1}%
264       \@bsphack%
265       \protected@edef\@tempa{{page}\{\the\c@page\}}% <--- should be protected
266       \setcounter{page}{1}%
267       \protected@edef\@tempb{\thepage}% <--- should be protected
268       \expandafter\setcounter\@tempa%
269       \cref@constructprefix{page}\{\cref@result\}%
270       \protected@write\@auxout{}{%
271         \string\newlabel{#1@cref}{{\cref@currentlabel}}%
272         {[{\@tempb} [{\arabic{page}}][{\cref@result}]\thepage}{}{}{}}% <---- five
273       \@esphack}%
274     \def\label@optarg[#1]#2{%
275       \cref@old@label{#2}%
276       \@bsphack%
277       \protected@edef\@tempa{{page}\{\the\c@page\}}% <--- should be protected
278       \setcounter{page}{1}%
279       \protected@edef\@tempb{\thepage}% <--- should be protected
280       \expandafter\setcounter\@tempa%
281       \cref@constructprefix{page}\{\cref@result\}%
282       \protected@edef\cref@currentlabel{%
283         \expandafter\cref@override@label@type%
284         \cref@currentlabel\@nil{#1}}%
285       \protected@write\@auxout{}{%
286         \string\newlabel{#2@cref}{{\cref@currentlabel}}%
287         {[{\@tempb} [{\arabic{page}}][{\cref@result}]\thepage}{}{}{}}% <---- five
288       \@esphack}%
289   }

```

cleveref patches and redefines \refstepcounter so that a call updates its data. This fails if like e.g. in longtable the counter is stepped with \kernel@refstepcounter. We therefore move the data setup into the label hook. As the hook is in a group we

have to smuggle the data out of it. <https://tex.stackexchange.com/a/722909/2388> and issue #1393

```

288      \newcommand\firstaid@ cref@smugglelabel{\let\cref@currentlabel\cref@gcurrentlabel@temp}
289      \newcommand\firstaid@ cref@updateelabedata[1]{%
290          \cref@constructprefix{#1}{\cref@result}%
291          \@ifundefined{cref@#1@alias}%
292              {\def\@tempa{#1}}%
293              {\def\@tempa{\csname cref@#1@alias\endcsname}}%
294          \protected@xdef\cref@gcurrentlabel@temp{%
295              [\@tempa] [\arabic{#1}] [\cref@result]%
296              \csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
297          \aftergroup\firstaid@ cref@smugglelabel
298      }

```

we test if `\@currentcounter` is empty for unnumbered sections

```

299      \newif\iftag@
300      \AddToHook{label}[firstaid/cleveref]
301      { \ifx
302          \@currentcounter\empty
303      \else
304          \iftag@ \else
305          \firstaid@ cref@updateelabedata{\@currentcounter}%
306          \fi
307      \fi}

```

Due to a bug correction in amsmath a patch in cleveref fails in LaTeX 2025-06-01, see gh 1684

```

308      \AddToHook{begindocument}[cleveref]
309      {
310          \IfPackageAtLeastT{amsmath}{2025-05-18}
311          {
312              \def\ltx@label#1{\cref@label{#1}}
313              \def\label@in@display@noarg#1{\cref@old@label@in@display{#1}}
314              \def\label@in@mmeasure@noarg#1{%
315                  \begin{group}
316                      \measuring@false%
317                      \cref@old@label@in@display{#1}%
318                  \end{group}%
319              }
320          }
321      }%
322 }

```

2.18 The `arydshln` package first aid

Making two internal commands robust to avoid expansion while constructing the array preamble.

```

323 \AddToHook{package/arydshln/after}[firstaid]{%
324     \FirstAidNeededT{arydshln}{sty}{2019/02/21 v1.76}%
325     {%
326         % add \protected
327         \protected\def\adl@@vlineL#1#2#3#4{\adl@ivline#4\@nil{#1}{#2}}%
328         \xdef\adl@colsL{\adl@colsL%
329             \@elt{#3}{\number\@tempcnta}{\number\@tempcntb}}%

```

```

330           {\adl@dashcolor}{\adl@gapcolor}}}}%
331 \protected\def\adl@@vlineR#1#2#3#4{\adl@ivline#4\@nil{#1}{#2}%
332     \xdef\adl@colsR{%
333         \@elt{#3}{\number\@tempcnta}{\number\@tempcntb}%
334         {\adl@dashcolor}{\adl@gapcolor}%
335     \adl@colsR}%
336 \let\adl@act@@vlineL\adl@@vlineL
337 \let\adl@act@@vlineR\adl@@vlineR
338 }%
339 }

```

2.19 The calc package first aid

The `calc` is not an external package, but for now we are removing a newly introduced incompatibility with `zref-perpage` here. At some point `amstext`, `zref-perpage`, `calc`, ... all need to be synced so that they do not overwrite the `\stepcounter` definition but safely hook into the kernel code. But that requires suitable hooks there, so has to wait.

```

340 \AddToHook{begindocument}[calc-noop]{}
341 \DeclareHookRule{begindocument}{calc-noop}{voids}{calc}

```

2.20 First aid after retiring the legacy mark mechanism

With the June 2025 release of L^AT_EX the legacy mark mechanism using `\@themark` with exactly two mark components has been removed and replaced by a more general mechanism. This affects a few packages and classes that had patched into the legacy code to extend it or to completely replace it. For now we do our best to keep that working, but mid-term all packages have to update to the new mechanism (and avoid low-level patching) in order to remain compatible with future adjustments.

For an analysis of the current situation see the github issues 1724 at <https://github.com/latex3/latex2e/issues/1724>.

We provide a dummy definition for `\@themark` because some classes expect it to be around. This prevents low-level errors but only helps if the class in question otherwise fully implement its own mark interface (as for example the AMS classes do).

```

342 \def\@themark{{}{}{}}
343 \AddToHook{class/smfout/after}[firstaid]{%
344   \FirstAidNeededT{smfout}{cls}{2021/03/28 v1.6}
345   Classe LaTeX pour les articles publiés par la SMF
346   {%
347     \def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}%
348     \def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}%
349   }%
350 \AddToHook{class/smfout/after}[firstaid]{%
351   \FirstAidNeededT{smfout}{cls}{2021/03/28 v1.6}
352   Classe LaTeX pour les monographies éditées par la SMF
353   {%
354     \def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}%
355     \def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}%
356   }%

```

2.21 First aid for `morewrites`

A recent change in L^AT_EX breaks the `morewrites` package. Below is a possible fix for this. This may not be the final version which is why it is currently placed here (largely to avoid to distribute another full dev release for no good reason).

```

357 \ExplSyntaxOn
358 \cs_set:Npn \__shipout_force_immediate_writes: {
359   \cs_gset_eq:NN \iow_shipout:Nn \iow_now:Nn
360   \cs_gset_eq:NN \lua_shipout:n \lua_now:n
361   \cs_gset_eq:NN \__kernel_write_saved: \write
362   \cs_gset:Npn \write {\immediate \__kernel_write_saved:}
363   \global\advance\c@page\m@ne
364 }
365 \ExplSyntaxOff
366 ⟨/kernel⟩

```

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| | | | |
|--|--|----------|---|
| <code>\Symbols</code> | <code>\@tempcntb</code> | 329, 333 | 84, 86, 88, 89, |
| <code>\@active@dq</code> | <code>\@themark</code> | 342 | 91, 98, 105, 106, |
| . 191, 192, 199, 200 | <code>\@typeset@protect</code> . | 213 | 115, 139, 148, |
| <code>\@auxout</code> | <code>\@unexpandable@protect</code> | | 153, 157, 188, |
| <code>\@bsphack</code> | | 216 | 196, 225, 229, |
| <code>\@combinefloats</code> | <code>\@vwid@append</code> | 183 | 236, 239, 244, |
| <code>\@currentcounter</code> | <code>\@vwid@eqmodefalse</code> . | 172 | 259, 300, 308, |
| . 302, 305 | <code>\@vwid@eqmodetrue</code> . | 173 | 323, 340, 343, 350 |
| <code>\@elt</code> | <code>\@vwid@offsets</code> | 176 | <code>\adl@@vlineL</code> 327, 336 |
| <code>\@empty</code> | <code>\@vwid@posteqp</code> | 173 | <code>\adl@@vlineR</code> 331, 337 |
| . 347, 348, 354, 355 | <code>\@vwid@postw</code> | 179 | <code>\adl@act@@vlineL</code> 336 |
| <code>\@esphack</code> | <code>\@vwid@preeqp</code> | 172 | <code>\adl@act@@vlineR</code> 337 |
| <code>\@firstoffive</code> | <code>\@vwid@resetb</code> | 181 | <code>\adl@colsL</code> 328 |
| <code>\@hspace</code> | <code>\@vwid@setoffsets</code> | 177 | <code>\adl@colsR</code> 332, 335 |
| <code>\@ifclassloaded</code> | <code>\@vwid@sift</code> | | <code>\adl@dashcolor</code> 330, 334 |
| <code>\@ifpackageloaded</code> | . 161, 169, 175, 185 | | <code>\adl@gapcolor</code> 330, 334 |
| <code>\@undefined</code> | <code>\@vwid@toppen</code> | 174 | <code>\adl@ivline</code> 327, 331 |
| <code>\@leftmark</code> | _ 208, 358, 361, 362 | | <code>\advance</code> 167, 363 |
| <code>\@one</code> | 145, 167 | | <code>\aftergroup</code> 297 |
| <code>\@nil</code> | 145, 167 | | <code>\AfterIncludeFile</code> 80 |
| <code>\@outputbox@attachfloats</code> | A | | <code>\AfterIncludes</code> 34 |
| . 151 | <code>\acsetup</code> | 233 | <code>\arabic</code> 270, 285, 295 |
| <code>\@par</code> | <code>\active</code> | 208 | <code>\AtBeginOfClasses</code> 40 |
| <code>\@rightmark</code> | <code>\ActiveUnderscore</code> . | 221 | <code>\AtBeginOfClassFile</code> 62 |
| <code>\@secondoffive</code> | <code>\AddToHook</code> | 27, 29, | <code>\AtBeginOfEveryFile</code> 26 |
| <code>\@spaces</code> | 31, 33, 35, 37, | | <code>\AtBeginOfFile</code> 44 |
| <code>\@tempa</code> | 39, 41, 43, 45, | | <code>\AtBeginOfIncludeFile</code> 76 |
| . 263, 266, 275, 278, 292, 293, 295 | 47, 52, 53, 59, | | <code>\AtBeginOfIncludes</code> 30 |
| <code>\@tempb</code> | 60, 66, 67, 73, | | |
| <code>\@tempcpta</code> | 74, 77, 79, 81, | | |

| | | |
|--|---|---|
| \AtBeginOfPackageFile | \DeclareHookRule 341 | G |
| 48 | \def 2, 3, 105, 143, 154, 161, 192, | \gdef 209 |
| \AtBeginOfPackages 36 | 200, 247, 249, 253, 255, 260, | \germanTeX 193 |
| \AtEndOfClasses 42 | 272, 292, 293, 312, 313, 314, | \global 141, 221, 363 |
| \AtEndOfClassFile 69 | 327, 331, 342, 347, 348, 354, 355 | \grmn@active@dq@ 191, 192, 199, 200 |
| \AtEndOfFile 46 | \dimen 122, 123 | H |
| \AtEndOfIncludeFile 78 | \dimen@ 164 | \hskip 127 |
| \AtEndOfIncludes 32 | \IfBooleanTF 155 | \hskip 155 |
| \AtEndOfPackageFile 55 | \IfDim 118, 119, 167, 176, 178, 180, 212, 214, 215, 217, 303, 304 | \hss 132 |
| \AtEndOfPackages 38 | \endcsname 248, 254, 293, 296 | I |
| B | \endgroup 135, 155, 222, 318 | \IfPackageAtLeastT 49, 56, 63, 70 |
| \BabelCaseHack 105 | \exp 9, 18 | \ifdim 118, 119, 163 |
| \begingroup 86, 124, 154, 207, 315 | \expandafter 145, 248, 249, 250, 251, 252, 254, 255, 256, 257, 258, 266, 278, 281, 296, 347, 348, 354, 355 | \ifinccsname 210 |
| \botmark 347, 354 | \ExplSyntaxOff 20, 96, 104, 365 | \ifmmode 214 |
| \BreakableUnderscore 214 | \ExplSyntaxOn 7, 90, 97, 357 | \ifnum 140, 144, 168, 172, 173, 174, 176, 179 |
| C | F | \IfVoid 167 |
| \c@page 263, 275, 363 | \fi 118, 119, 142, 146, 163, 167, 171, 172, 173, 182, 184, 214, 218, 219, 306, 307 | \ifx 213, 216, 301 |
| \catcode 208 | \firstaid@ cref@smugglelabel 288, 297 | \immediate 362 |
| \count 140, 141, 144 | \firstaid@ updatelabel 289, 305 | \insc@unt 140, 141 |
| \count@ 165, 172, 173, 174, 176, 179 | \FirstAidNeededT 7, 85, 107, 116, 149, 158, 189, 197, 226, 230, 240, 245, 324, 344, 351 | \iow 359 |
| \cpageref@getref 253 | \firstmark 348, 355 | K |
| \cref@constructprefix 267, 279, 290 | \FN@allmarks 143, 145 | \kern 123 |
| \cref@currentlabel 269, 280, 282, 284, 288 | G | L |
| \cref@gcurrentlabel@temp 288, 294 | \label@in@display@noarg 313 | \label@in@mmeasure@noarg 314 |
| \cref@getref 247 | \label@noarg 260 | \label@optarg 272 |
| \cref@label 312 | \label@optarg 272 | \lastbox 166 |
| \cref@old@label 261, 273 | \lastskip 162, 163 | \lastkern 164 |
| \cref@old@label@in@display 313, 317 | \TeXFirstAidDate 2, 5 | \lastpenalty 165 |
| \cref@override@label@type 281 | \TeXFirstAidVersion 3, 5 | \leavevmode 121 |
| \cref@result 267, 270, 279, 285, 290, 295 | D | \leftmark 347, 354 |
| \CROP@genreflect 120 | \declare@file@substitution 23 | \let 110, 112, 151, 169, 175, 191, 199, 221, 248, 254, 288, 336, 337 |
| \CROP@horigin 122 | \DeclareDocumentCommand 48, 55, 62, 69 | \lua 360 |
| \cs 8, 92, 93, 94, 99, 100, 101, 358, 359, 360, 361, 362 | \firstmark 348, 355 | M |
| \csname 248, 254, 293, 296 | \FN@allmarks 143, 145 | \ltx@label 312 |
| D | E | \ltx@label 312 |
| \declare@file@substitution 23 | \edef 155 | \ltx@label 312 |
| \DeclareDocumentCommand 48, 55, 62, 69 | \else 118, 119, 167, 176, 178, 180, 212, 214, 215, 217, 303, 304 | \ltx@label 312 |

| | | | |
|--|--|---------------------------|---------------------------|
| | M | \protected | \space |
| | \m@ne | 363 . 209, 326, 327, 331 | \stockheight |
| | \mathcode | 89 \protected@edef 263, | \stockwidth |
| | \measuring@false .. | 316 265, 275, 277, 280 | \str |
| | | \protected@write .. | \string ... 211, 269, 284 |
| | N | 268, 283 | T |
| | \newcommand 26, 28, 30, | \protected@xdef ... 294 | \tex ... 93, 94, 100, 101 |
| | 32, 34, 36, 38, | \ProvidesFile 4 | \the 155, 263, 275 |
| | 40, 42, 44, 46, | \ProvidesPackage ... 206 | \thepage |
| | 76, 78, 80, 288, 289 | | . 265, 270, 277, 285 |
| | \newif | 299 | \typeout |
| | \newlabel | 269, 284 | 10, 11 |
| | \ngermanTeX | 201 | |
| | \noexpand | 216 | U |
| | \number ... 145, 329, 333 | \relax ... 155, 169, 175 | \unkern |
| | \numexpr | 145 | \unpenalty |
| | O | \renewcommand .. 109, 120 | \unskip |
| | \obeyedline | 110 | \RequirePackage 226, 237 |
| | \obeylines | 111 | \use |
| | P | \SB@par | \UseName 232, 242 |
| | \PackageWarning ... 170 | \SB@obeylines ... 109 | V |
| | \paperheight ... 119, 128 | \SB@par | \vbox |
| | \paperwidth ... 118, 127 | \setbox | 128 |
| | \pgfhookintoshipout 99 | \setcounter | \vss |
| | \pgfpages@interceptshipout ... 94, 101 | \setlength | 130 |
| | | 264, 266, 276, 278 | |
| | | 154 | W |
| | \pgfpages@originalshipout | \shipout | \write |
| | | 92 | 361, 362 |
| | | 92, 93, 100 | |
| | \protect | \sift@deathcycles .. | X |
| | 192, | 167, 168 | \x |
| | 200, 213, 216, 217 | \skip@ ... 154, 155, 162 | 155 |
| | | | \xdef |
| | | | 328, 332 |
| | Z | | |
| | \z@ ... 163, 166, 167, 181 | | |