

# customenvs [en]

Some custom environments,  
or small patches.

Version 0.40d -- 06/07/2025

<https://github.com/cpierquet/latex-packages/tree/main/customenvs>

<https://forge.apps.education.fr/pierquetcedric/packages-latex>

---

## Contents

<b>1</b>	<b>History</b>	<b>1</b>
<b>2</b>	<b>The package customenvs</b>	<b>2</b>
2.1	Idea . . . . .	2
2.2	Loading . . . . .	2
2.3	Subpackage customenvs-tikzpictos (v0.1.4) . . . . .	3
<b>3</b>	<b>Answers for a MCQ</b>	<b>4</b>
3.1	Idea . . . . .	4
3.2	Examples . . . . .	4
<b>4</b>	<b>List with picked elements (random or not)</b>	<b>6</b>
4.1	Global use . . . . .	6
4.2	Examples . . . . .	6
<b>5</b>	<b>Pencil of skills</b>	<b>8</b>
5.1	Global use . . . . .	8
5.2	The macro . . . . .	8
5.3	Examples . . . . .	8
<b>6</b>	<b>Score banner</b>	<b>10</b>
6.1	Global use . . . . .	10
6.2	The macro . . . . .	10
<b>7</b>	<b>SMS conversation</b>	<b>11</b>
7.1	Global use . . . . .	11
7.2	The environment . . . . .	11
7.3	Macros for the bubbles . . . . .	11
7.4	Examples . . . . .	12
<b>8</b>	<b>Title banner</b>	<b>14</b>
8.1	Global usage . . . . .	14
8.2	Examples . . . . .	14
<b>9</b>	<b>Various commands</b>	<b>16</b>
9.1	Difficulty levels with stars (fontawesome5) . . . . .	16
9.2	Difficulty levels with stars (tikz) . . . . .	16
9.3	Flared arrow . . . . .	16
9.4	Small markerbox . . . . .	17
9.5	Annotate an image . . . . .	17

## 1 History

v0.40d : Code enhancements (compatibility with twemojis) + customenvs-tikzpictos v0.1.4  
v0.40c : PictoClippy (customenvs-tikzpictos v0.1.3) + Lengths macros  
v0.40b : PictoCalendar (customenvs-tikzpictos v0.1.2) + enhancements  
v0.40a : PictoTraffic (customenvs-tikzpictos v0.1.1) + enhancements  
v0.3.7 : Auxiliary package customenvs-tikzpictos for pictograms  
v0.3.6 : Picto *bullseye+arrow*  
v0.3.5 : Bugfix + pre-compatibility with fa5/fa6  
v0.3.4 : Pictoskill  
v0.3.3 : Annotate image  
v0.3.2 : Alt version of title banner  
v0.3.1 : Box for MCQ  
v0.3.0 : Bugfix with beamer  
v0.2.7 : Key for mixing answers in MCQ  
v0.2.6 : Whell of skills, speedometer  
v0.2.5 : Bugfix with exercices ([fr] macro)  
v0.2.4 : Small box *marker*  
v0.2.3 : Highway signs + sold banners (see [fr] doc)  
v0.2.2 : Flared arrow, with TikZ  
v0.2.1 : Enhancements for *stars skills* + AutoGrid for TikZ (see [fr] doc)  
v0.2.0 : Skills with stars (fontawesome5 or TikZ)  
v0.1.9 : Title banner  
v0.1.8 : Score banner  
v0.1.7 : Small patch for Vignette macro (see [fr] documentation)  
v0.1.6 : Small patches for displayskip + pas-tableur (see [fr] documentation)  
v0.1.5 : New macros for boxes with tcolorbox (see [fr] documentation)  
v0.1.4 : Create a SMS conversation  
v0.1.3 : Environment for exercise(s) (in french doc)  
v0.1.2 : Pencil of skills  
v0.1.1 : Skills table (only french for the moment...)  
v0.1.0 : Initial version

## 2 The package customenvs

### 2.1 Idea

The idea is to propose some classics environments with customizations (some are, for the moment, only in french) :

- write in *multicols*, with spacings enhancements ;
- present answers for a *MCQ* ;
- create a list with *chosen items* (randomly or by numbers) ;
- present a skill table.

The global idea is to propose *user-friendly* environments, with explicit customizations, without using verbose syntax ; but there's other solutions, using for example `\vspace` ou `\setlength` or `spacingtricks` package.

### 2.2 Loading

The package loads within the preamble with `\usepackage{customenvs}`.

Loaded packages are

- `xstring`, `simplekv`, `listofitems`, `randomlist` and `xintexpr` ;
- `enumitem` ;
- `multicol` ;
- `tabularray` ;
- `fontawesome` ;

Due to limitations, `enumitem/multicol/tabularrayfontawesome5/6` can be *unloaded* by `customenvs` (user must load them manually) via options :

- `<beamer>` for using with beamer ;
- `<noenum>` ;
- `<nomulticol>` ;
- `<notblr>` ;
- `<nofa>`.

```
%with all packages
\usepackage{customenvs}

%with option to no load some packages
\usepackage[option(s)]{customenvs}
```















2.3 Subpackage customenvs-tikzpictos (v0.1.4)

The package `customenvs-tikzpictos`, loaded within `customenvs` (but can be loaded independently), proposes small pictograms.

```
%\usepackage{customenvs-tikzpictos} %only if for standalone

\tikzpicto%
  [keys]
  <tikz options>
  {type=params}

%type= wifi/network/stars/speedo/bullseye/skills/pill/calendar
%params= nb/nblevels (except bullseye) or day/month (calendar)
%key height= len / auto (without depth) / dauto (with depth)
```

Wifi	
Wifi (bars)	
Network	
Stars	
Speedometer	
BullsEye	
Battery	
Battery (flip)	
Skills	
Pill	
TrafficLight	
MiniCalendar	
Clippy	
Dball	

## 3 Answers for a MCQ

### 3.1 Idea

The idea is to propose an environment to present answers for a MCQ with `tabularray` (and not `multicols`). It's possible to use 2, 3 or 4 answers (and with 4 answers it's possible to use 2 columns.)

```
\AnswersMCQ[options]{list of answers}<tblr options>
```

The available `options` are :

- `Width` : `0.99\linewidth` by default ;
- `Lines` : `false` by default ;
- `SpaceCR` for Columns/Rows spacing, within `col/row` or `global` : `6pt/2pt` by default ;
- `NumCols`, 2 or 4 : `4` by default ;
- `Labels` for the labels : `a.` by default ;
  - with `box` to use a *Box* ;
  - with `a` to *enumerate* `a b c d` ;
  - with `A` to *enumerate* `A B C D` ;
  - with `1` to *enumerate* `1 2 3 4` ;
- `FontLabels` : `\bfseries` by default ;
- `SpaceLabels` : `\kern5pt` by default ;
- `Shuffle`, for mixing answers : `false` by default ;
- `Swap`, for ACBD instead of ABCD : `false` by default.

The list of answers must be given within `answA $ answB $ ...`.

Specific options for `tblr` are given between last optionnal argument, between `<...>`.

### 3.2 Examples

```
%default output
```

```
\AnswersMCQ{Answer A $ Answer B $ Answer C $ Answer D}
```

a. Answer A	b. Answer B	c. Answer C	d. Answer D
-------------	-------------	-------------	-------------

```
\AnswersMCQ[Lines]{Answer A $ Answer B $ Answer C $ Answer D}
```

```
\AnswersMCQ[Lines,Shuffle]{Answer A1 $ Answer B1 $ Answer C1 $ Answer D1}
```

```
\AnswersMCQ[Lines,Shuffle]{Answer A2 $ Answer B2 $ Answer C2 $ Answer D2}
```

a. Answer A	b. Answer B	c. Answer C	d. Answer D
a. Answer A1	b. Answer C1	c. Answer D1	d. Answer B1
a. Answer C2	b. Answer A2	c. Answer B2	d. Answer D2

```
\AnswersMCQ[Lines,Labels=(1.),SpaceLabels={~~~}]{Answer A $ Answer B $ Answer C}
```

(1.) Answer A	(2.) Answer B	(3.) Answer C
---------------	---------------	---------------

```
\AnswersMCQ[Labels={A.},FontLabels={\color{red}\bfseries}]%
{Answer A § Answer B § Answer C § Answer D}
```

**A.** Answer A                      **B.** Answer B                      **C.** Answer C                      **D.** Answer D

```
\AnswersMCQ[Labels={1.},FontLabels={\color{red}\bfseries}]%
{Answer A § Answer B § Answer C § Answer D}
```

**1.** Answer A                      **2.** Answer B                      **3.** Answer C                      **4.** Answer D

```
\AnswersMCQ[NumCols=2,Labels={A.},FontLabels={\color{red}\bfseries}]%
{Answer A § Answer B § Answer C § Answer D}
```

**A.** Answer A    **C.** Answer C  
**B.** Answer B    **D.** Answer D

```
\AnswersMCQ[NumCols=2,Swap,Labels={A.},FontLabels={\color{red}\bfseries}]%
{Answer A § Answer B § Answer C § Answer D}
```

**A.** Answer A    **B.** Answer B  
**C.** Answer C    **D.** Answer D

```
\AnswersMCQ[Lines,NumCols=2,SpaceCR=6pt/10pt,Labels=box]%
{Answer A § Answer B § Answer C § Answer D}
```

<input type="checkbox"/> Answer A	<input type="checkbox"/> Answer C
<input type="checkbox"/> Answer B	<input type="checkbox"/> Answer D

```
% checkbox is \def\MCQanswersbox{\raisebox{-0.2ex}{\faSquare[regular]}}
\AnswersMCQ[Width=10cm,NumCols=2,Lines]%
{${\displaystyle\frac{1}{x}} § $1+{\displaystyle\frac{1}{x}} § $-2x^2+5$ § $-\infty$}
<rows={1.5cm}>
```

a. $\frac{1}{x}$	c. $-2x^2 + 5$
b. $1 + \frac{1}{x}$	d. $-\infty$

## 4 List with picked elements (random or not)

### 4.1 Global use

The idea is to :

- create a list of items, the base for choices ;
- print the list with picked items.

```
\CreateItemsList{list}{macro}{listname}
```

```
\ListItemsChoice[keys]{macro}{listname}(numbers)<enumitem options>!beamer options!
```

The available **keys** are :

- **Type** : **enum** or **item** ;
- **Random** : **false** by default.

The second argument, mandatory and between **{...}** is the macro for the list.

The third argument, mandatory and between **{...}** is the name of the list.

The fourth argument, mandatory and between **(...)** give :

- the number of random items to display, with **Random=true** ;
- the numbers of picked items, within **num1,num2,...**.

The next argument, optional and between **<...>** gives specific options to **enumitem** environment.

The last argument, between **!!!** gives specific options to **enumitem** environment with **beamer**.

Controls are done :

- to verify that the list doesn't exist (for the creation) ;
- to verify that that the list still exist (for the display).

### 4.2 Examples

```
%creation of list ListItems, with macro \mylistofitems
\CreateItemsList%
  {Answer A,Answer B,Answer C,Answer D,Answer E,Answer F,Answer G,Answer H}%
  {\mylistofitems}{ListItems}
```

```
%items random
\ListItemsChoice[Random]{\mylistofitems}{ListItems}(5)
```

1. Answer H
2. Answer E
3. Answer C
4. Answer D
5. Answer G

```
%items picked
\ListItemsChoice{\mylistofitems}{ListItems}(1,4,3,8,2)
```

1. Answer A
2. Answer D
3. Answer C
4. Answer H
5. Answer B

```
%creation of list ListItemsB, with macro \mylistofitemsb
\CreateItemsList%
  { $\int_0^1 x^2 dx$ },{ $\int_0^1 x^3 dx$ },{ $\int_0^1 x^4 dx$ },...}%
  {\mylistofitemsb}{ListItemsB}
```

```
%items picked
\ListItemsChoice[Type=item]{\mylistofitemsb}{ListItemsB}(7,2,1,5,3)<label=$--$>
```

$$-- \int_0^1 x^8 dx$$

$$-- \int_0^1 x^3 dx$$

$$-- \int_0^1 x^2 dx$$

$$-- \int_0^1 x^6 dx$$

$$-- \int_0^1 x^4 dx$$

## 5 Pencil of skills

### 5.1 Global use

The idea is to :

- present of list of categories and skills ;
- presented like a pencil.

The code (within CC-BY-SA 4.0 license) is adapted from :

<https://tex.stackexchange.com/questions/504092/replicating-a-fancy-bordered-text-style-in-latex/504145#504145>

```
\PencilSkills[keys]<tikz options>{listofskills}
```

The style is globally fixed, but there's some customization available.

### 5.2 The macro

Available `keys` are :


- `FontCateg` : font for the categories ;
- `FontBlock` : font for the skills ;
- `Colors` : list of category's colors  
`BgCateg1/FgCateg1,BgCateg1/FgCateg1,...`  
(if `FgCateg1` est missing, `black` is used)
- `BlockWidth` : width of skill's block ;
- `Scale` : global scale
- `BlackWhite` : boolean for B&W.

The second argument, optional and between `<...>` gives specific options to `enumitem` environment.

The last argument, mandatory and between `(...)` give the list of categories/skills, within `Categ1/ListSkills1,Categ2/ListSkills2,...`.

### 5.3 Examples

```
%default output  
\PencilSkills{Search/Skill 1\\ Skill 2,Model/{Skill 1\\ Skill 2}}
```



```
\PencilSkills[Scale=0.75]%
  {Search/Skill 1\\Skill 2,Model/{Skill 1\\Skill 2},%
  Represent/{Skill 1\\Skill 2},Calculate/{Skill 1\\Skill 2},%
  Reason/{Skill 1\\Skill 2},Communicate/{Skill 1\\Skill 2}}
```

#### Search

Skill 1  
Skill 2

#### Model

Skill 1  
Skill 2

#### Represent

Skill 1  
Skill 2

#### Calculate

Skill 1  
Skill 2


#### Reason

Skill 1  
Skill 2

#### Communicate

Skill 1  
Skill 2

```
\PencilSkills[Scale=0.75,BlockWidth=3cm]<rotate=90>{
  Search/Skill 1\\Skill 2,Model/{Skill 1\\Skill 2}}
\hspace{1cm}
\PencilSkills[Scale=0.75,BlockWidth=3cm]<rotate=-90>{
  Search/Skill 1\\Skill 2,Model/{Skill 1\\Skill 2}}
\hspace{1cm}
\PencilSkills[Scale=0.75,BlockWidth=3cm,BlackWhite]<rotate=45>{
  Search/Skill 1\\Skill 2,Model/{Skill 1\\Skill 2}}
```



## 6 Score banner

### 6.1 Global use

The idea is to insert a score banner, with customization.

```
ScoreBanner[keys]{number}
```

```
%default output  
\ScoreBanner{}
```



### 6.2 The macro

Available `keys` are :

- `Height` : height of the banner (without the legend) ; `1` by default
- `Ratio` : ratio of boxes ; `0.6` by default
- `Symbols` : labels ; `A,B,C,D,E` by default
- `Legend` : legend (uppercase) ; `score` by default ;
- `Font` : global font ; `\bfseries\sffamily` by default
- `ShowLegend` : boolean for the legend ; `false` by default ;
- `Colors` : colors for boxes ;  
`colorNS1,colorNS2,colorNS3,colorNS4,colorNS5` by default ;
- `ScaleSymbols` : scale H/V of labels ; `1.25,1.65` by default ;
- `Colbg` : background color for select box ; `white` by default.

If the list of colors doesn't fill all the boxes, `lightgray` color is used.

```
\ScoreBanner[Legend=Geometry,Height=2]{4}
```



```
%bg of lower part is yellow!25  
\def\lstcouleurs{colorNS1,colorNS2,colorNS3,colorNS4,colorNS5,purple}  
\ScoreBanner%  
[ScaleSymbols={1.33,2},Height=3.25,ShowLegend=false,Ratio=0.75,  
Symbols={1,2,3,4,5,6},Colors=\lstcouleurs,  
Colbg=yellow!25]{1}
```



## 7 SMS conversation

### 7.1 Global use

The idea is to present a conversation of SMS.

```
\begin{ChatSMS}[keys]{name}  
  \InSMS(*){time}{msg}  
  \OutSMS*(*){time}{msg}  
\end{ChatSMS}
```

The style is globally fixed, but there's some customization available.

### 7.2 The environment

Available `keys` are :

- `height` : height of the window (auto or specific) ; `auto` by default
- `width` : width of the window ; `7cm` by default
- `margin` : margin (L or R) for the bubble `1.5cm` by default
- `color` : *main* color (banner) ; `teal!75!cyan!75!white` by default ;
- `colback` : color for background ; `lightgray!5` by default
- `colorin` : color for incoming SMS ; `lime!25` by default
- `colorout` : color for outgoing SMS ; `teal!25` by default
- `writetxt` : text of sending zone ; `Write` by default
- `fonttxt` : bubble's font ; `\normalfont` by default
- `avatar` : avatar of contact ; `\faAddressCard` by default
- `dispavatar` : boolean for displaying avatar near the bubbles ; `false` by default
- `blackwhite` : boolean pour black&white. `false` by default

The argument, mandatory and between `(...)` give the name of the contact.


### 7.3 Macros for the bubbles

Regarding the bubble creation commands, `\InSMS` and `\OutSMS`:

- the *starred* version does not display the *checkmarks* of *good reception*;
- the first mandatory argument is the time to display ;
- the second mandatory argument is the message to display (including multi-lines).

## 7.4 Examples


```
%with a personal image
\begin{ChatSMS}%
  [width=6cm,fonttxt=\sffamily,height=10cm,avatar=img/android,dispavatar]{CP}
  \InSMS{19:23}{Hi !}
  \OutSMS{19:23}{Hi !\ \ How are you ?}
  \InSMS{19:25}{Just a problem with a math question\ldots}
  \OutSMS{19:26}{Wanna help ??}
  \InSMS{19:28}{Yes, I need to compute  $\int_0^1 x^2 e^{-x} dx$ \ldots}
  \OutSMS*{19:30}{Take care !!}
\end{ChatSMS}
```



```

\begin{ChatSMS}%
  [width=8cm,fonttxt=\sffamily,avatar=\faCanadianMapleLeaf,blackwhite]{CP}
  \InSMS{19:23}{Hi !}
  \OutSMS{19:23}{Hi !\ How are you ?}
  \InSMS{19:25}{Just a problem with a math question\ldots}
  \OutSMS{19:26}{Wanna help ??}
  \InSMS{19:28}{Yes, I need to compute  $\int_0^1 x^2 e^{-x} dx$ \ldots}
  \OutSMS*{19:30}{Take care !!}
\end{ChatSMS}

```



## 8 Title banner

### 8.1 Global usage

The idea is to propose a banner, made with TikZ, to present for example a title. The global style is fixed, but few customization are possible.

```
\tkzBannerTri[keys]{number}{title}
```

```
\tkzBannerTri{01}{Title of document}
```



Available keys are :

- `height` (2.5em by default)
- `width` (\linewidth by default)
- `blockwidth` (2.75em by default, but can be set to `auto`)
- `coltxt` (white by default)
- `fonttxt`
- `swap` (false by default, for an other style )
- `maincolor` (darkgray by default)
- `collight` (darkgray!25 by default)
- `colmedium` (darkgray!50 by default)
- `coldark` (darkgray by default)
- `logo`
- `type`
- `dispblock` (true by default)
- `num` (true by default)
- `customtype`
- `custommulti` (false by default)

### 8.2 Examples

```
\tkzBannerTri  
[maincolor=red,type=EXERCISES,blockwidth=auto,logo=\faAddressBook]  
{7}{My doc}
```



```
\tkzBannerTri  
[maincolor=red,type=EXERCISES,blockwidth=5em,logo=\faAddressBook]  
{7}{My doc}
```



```
\tkzBannerTri
[maincolor=red,type=EXERCISES,blockwidth=auto,logo=\faAddressBook,swap]
{07}{My doc}
```

EXERCISES

07

My doc



```
\tkzBannerTri
[dispblock=false,maincolor=teal,logo=\faSchool]
{}{My doc}
```

My doc



```
\tkzBannerTri
[maincolor=olive,customtype=TP,blockwidth=4em,logo=\faAddressBook,height=4em]
{7}{My doc}
```

TP

My doc



```
\tkzBannerTriAlt
[maincolor=violet,type=UE3.1,blockwidth=1.25cm,logo=\faGraduationCap,height=1.25cm]
{TP}{My doc}
```

UE3.1  
TP

My doc



## 9 Various commands

### 9.1 Difficulty levels with stars (fontawesome5)

```
\DiffLevelStars[max level (3)]{level}
```

```
\DiffLevelStars{0}\par
\DiffLevelStars{2.5}\par
\textcolor{teal}{\LARGE\DiffLevelStars[5]{4}}\par
\DiffLevelStars[5]{1.5}\par
```



### 9.2 Difficulty levels with stars (tikz)

```
\tkzLevelStars[colframe=...,colback=...,offset=...,maxlevel=...,valign=...]{level}
```


```
\tkzLevelStars{2.5}\par
{\LARGE We ty inline \tkzLevelStars{2.25} with score 2.25}\par
{\LARGE We ty inline \tkzLevelStars[valign=false]{1.75} with score 1.75}\par
\tkzLevelStars[colframe=red,colback=yellow,maxlevel=5]{3}
```

★★★  
We ty inline ★★☆☆ with score 2.25  
We ty inline ★★☆☆ with score 1.75  
★★★★☆☆

### 9.3 Flared arrow

```
\tkzFlaredArrow[%
  color=...,           %color of arrow
  arrowsize=...,       %size (auto or H/W )
  bend=...,            %empty for straight or left/... or right/...
  thickness=...,       %size for the beginning
  factor=...,          %factor for calculing size for ending
  arrowstyle=...,      %style (arrows.meta)
  move=...             %boolean for moving instead coordinates
]%
{begin}{end or move}
```


```
%arrow 0.5mm -> 1.25mm
\begin{tikzpicture}
\tkzFlaredArrow%
  [thickness=0.5mm,factor=2.5,bend=left/30,color=red,arrowstyle=Triangle]%
  {0,0}{5,1.5}
\end{tikzpicture}
```



```

\begin{tikzpicture}
  \draw[thin,lightgray] (-3,-1) grid (5,5) ;
  \coordinate (A) at (0,0) ; \coordinate (B) at (4,1) ;
  \coordinate (C) at (1,1) ; \coordinate (D) at (5,4) ;
  \coordinate (E) at (0,1) ; \coordinate (F) at (0,5) ;
  \coordinate (G) at (-2,0) ;
  \tkzFlaredArrow[color=green,arrowstyle=Triangle]{A}{B}
  \tkzFlaredArrow[color=blue,bend=right/10]{D}{C}
  \tkzFlaredArrow%
    [color=red,bend=left/45,arrowstyle=Stealth,thickness=0.1mm,factor=10]%
    {-2,1}{0,4}
  \tkzFlaredArrow%
    [color=red,bend=right/45,thickness=0.1mm,factor=10,arrowstyle=Stealth]%
    {-2,1}{0,4}
  \tkzFlaredArrow[color=teal,move,bend=left/10]{-3,-1}{5,1}
\end{tikzpicture}

```



## 9.4 Small markerbox

```
\tbcmarker[color=...,width=...,font=...]{text}
```

```
\tbcmarker{my text}
```

```
\tbcmarker[color=olive,font=\normalfont\normalsize]{my text}
```

## 9.5 Annotate an image

The idea is to provide a way of annotating an image, using an environment and a command which are linked to TikZ.


```

\begin{imgannotate}[keys][includegraphics options]{imagefile with extension}
  \puttxttonimg[tikz node options]{coordinates}{txt}
  \puttxttonimg*[tikz node options]{coordinates within percentage}{txt}
\end{imgannotate}


%===keys
%clip=...      : boolean for clipping img
%node=...      : node name for reusing (remember picture)
%grid=...      : optionnal value for showing helping grid
%subgrid=...   : integer value for subgrid
%gridcolor=... : grid color

```

```
%\usepackage[auto,outline]{contour}
\begin{imgannotate}[grid=1][height=4cm]{example-image.png}
  \puttxtoning[scale=5,rotate=30]
    {1,1}{\contourlength{0.05em}\color{white}\contour{black}{\pi}}
  \puttxtoning*[scale=1.5,rotate=-15]
    {0.66,0.75}{\contourlength{0.025em}\color{violet}\contour{yellow}{Pythagore}}
\end{imgannotate}
```



```
\begin{imgannotate}[node=IMGTEST][height=5cm]<rotate=10>{example-image-golden.pdf}
  %tikz usual commands
  \draw (IMGTEST.center) node[above=5mm,font=\Huge\ttfamily\bfseries,text=blue] {TEST1} ;
  \draw (IMGTEST.north west) node[draw,thick,red,inner sep=0.5mm,below
right=2.5mm,font=\LARGE\sffamily\bfseries,text=red] {TEST2} ;
\end{imgannotate}
```



## 9.6 Lengths

```
\getwideststring[\macro]{elt1,elt2,...,eltn}

\halignmakebox[align option]{elt}{list of elements}
```

```
%widest string (\tmpwideststring by default)
\getwideststring{Exercise 1,Evaluation 2,Test n°3}\the\tmpwideststring
```

60.69586pt

```
%without
\sffamily\Large
Exercise 1 (10 points)\
Evaluation 2 (8 points) \
Test n°3 (4 points)
```

Exercise 1 (10 points)  
Evaluation 2 (8 points)  
Test n°3 (4 points)

```
%with
\sffamily\Large
\halignmakebox[l]{Exercise 1}{Exercise 1,Evaluation 2,Test n°3}
(\halignmakebox[r]{10}{10,8,4} points)

\halignmakebox[l]{Evaluation 2}{Exercise 1,Evaluation 2,Test n°3}
(\halignmakebox[r]{8}{10,8,4} points)

\halignmakebox[l]{Test n°3}{Exercise 1,Evaluation 2,Test n°3}
(\halignmakebox[r]{4}{10,8,4} points)
```

Exercise 1 (10 points)  
 Evaluation 2 ( 8 points)  
 Test n°3 ( 4 points)

```
%width
\storewidthtolength[delta]{box}{\macro}
%height
\storeheighttolength[delta]{box}{\macro}
%totalheight
\storetotalheighttolength[delta]{box}{\macro}
%depth
\storedepthtolength[delta]{box}{\macro}
```

```
\def\tmpbox{\large $1+\frac{1}{x}$}
%
\storewidthtolength{\tmpbox}{\mytmpboxwidth}\the\mytmpboxwidth


\storewidthtolength[10pt]{\tmpbox}{\mytmpboxwidthdelta}\the\mytmpboxwidthdelta

\storeheighttolength{\tmpbox}{\mytmpboxheight}\the\mytmpboxheight

\storetotalheighttolength{\tmpbox}{\mytmpboxtoheight}\the\mytmpboxtoheight

\storedepthtolength{\tmpbox}{\mytmpboxdepth}\the\mytmpboxdepth
```

27.53175pt  
 37.53175pt  
 9.88034pt  
 14.01843pt  
 4.13809pt



```
%starred version with box (tikz)
\fittexttobox(*){text}{width}{height}
```

%with box

```
\fittexttobox*{PHONE}{2cm}{1cm}\\  
\fittexttobox*{\bfseries\sffamily PHONE}{7cm}{1cm}\\  
\fittexttobox*{PHONE}{3cm}{1cm}\\  
\fittexttobox*{\ttfamily PHONE}{3cm}{1cm}\\  
\fittexttobox*{PHONE}{2cm}{2cm}\\  
\fittexttobox*{CONGRATULATIONS}{10cm}{3.5cm}\\  
\fittexttobox*{CONGRATULATIONS}{14cm}{1.25cm}
```

PHONE

**PHONE**

PHONE

PHONE

PHONE

CONGRATULATIONS

CONGRATULATIONS

%w/o box

```
\fittexttobox{PHONE}{2cm}{1cm}\\  
\fittexttobox{\bfseries\sffamily PHONE}{7cm}{1cm}\\  
\fittexttobox{PHONE}{3cm}{1cm}\\  
\fittexttobox{\ttfamily PHONE}{3cm}{1cm}\\  
\fittexttobox{PHONE}{2cm}{2cm}\\  
\fittexttobox{CONGRATULATIONS}{10cm}{3.5cm}\\  
\fittexttobox{CONGRATULATIONS}{14cm}{1.25cm}
```

PHONE

**PHONE**

PHONE

PHONE

PHONE

CONGRATULATIONS

CONGRATULATIONS