

The `calc` package

Infix notation arithmetic in L^AT_EX*

Kresten Krab Thorup, Frank Jensen (and Chris Rowley)

2025/03/01

This file is maintained by the L^AT_EX Project team.
Bug reports can be opened (category `tools`) at
<https://latex-project.org/bugs.html>.

Abstract

The `calc` package reimplements the L^AT_EX commands `\setcounter`, `\addtocounter`, `\setlength`, and `\addtolength`. Instead of a simple value, these commands now accept an infix notation expression.

1 Introduction

Arithmetic in T_EX is done using low-level operations such as `\advance` and `\multiply`. This may be acceptable when developing a macro package, but it is not an acceptable interface for the end user.

This package introduces proper infix notation arithmetic which is much more familiar to most people. The infix notation is more readable and easier to modify than the alternative: a sequence of assignment and arithmetic instructions. One of the arithmetic instructions (`\divide`) does not even have an equivalent in standard L^AT_EX.

The infix expressions can be used in arguments to macros (the `calc` package doesn't employ category code changes to achieve its goals).¹

2 Informal description

Standard L^AT_EX provides the following set of commands to manipulate counters and lengths [2, pages 194 and 216].

`\setcounter{ctr}{num}` sets the value of the counter *ctr* equal to (the value of) *num*. (Fragile)

*We thank Frank Mittelbach for his valuable comments and suggestions which have greatly improved this package.

¹However, it therefore assumes that the category codes of the special characters, such as `(*/)` in its syntax do not change.

`\addtocounter{ctr}{num}` increments the value of the counter *ctr* by (the value of) *num*. (Fragile)

`\setlength{cmd}{len}` sets the value of the length command *cmd* equal to (the value of) *len*. (Robust)

`\addtolength{cmd}{len}` sets the value of the length command *cmd* equal to its current value plus (the value of) *len*. (Robust)

(The `\setcounter` and `\addtocounter` commands have global effect, while the `\setlength` and `\addtolength` commands obey the normal scoping rules.) In standard L^AT_EX, the arguments to these commands must be simple values. The `calc` package extends these commands to accept infix notation expressions, denoting values of appropriate types. Using the `calc` package, *num* is replaced by $\langle \text{integer expression} \rangle$, and *len* is replaced by $\langle \text{glue expression} \rangle$. The formal syntax of $\langle \text{integer expression} \rangle$ and $\langle \text{glue expression} \rangle$ is given below.

In addition to these commands to explicitly set a length, many L^AT_EX commands take a length argument. After loading this package, most of these commands will accept a $\langle \text{glue expression} \rangle$. This includes the optional width argument of `\makebox`, the width argument of `\parbox`, `minipage`, and a `tabular` p-column, and many similar constructions. (This package does not redefine any of these commands, but they are defined by default to read their arguments by `\setlength` and so automatically benefit from the enhanced `\setlength` command provided by this package.)

In the following, we shall use standard T_EX terminology. The correspondence between T_EX and L^AT_EX terminology is as follows: L^AT_EX counters correspond to T_EX's count registers; they hold quantities of type $\langle \text{number} \rangle$. L^AT_EX length commands correspond to T_EX's dimen (for rigid lengths) and skip (for rubber lengths) registers; they hold quantities of types $\langle \text{dimen} \rangle$ and $\langle \text{glue} \rangle$, respectively.

T_EX gives us primitive operations to perform arithmetic on registers as follows:

- addition and subtraction on all types of quantities without restrictions;
- multiplication and division by an *integer* can be performed on a register of any type;
- multiplication by a *real* number (i.e., a number with a fractional part) can be performed on a register of any type, but the stretch and shrink components of a glue quantity are discarded.

The `calc` package uses these T_EX primitives but provides a more user-friendly notation for expressing the arithmetic.

An expression is formed of numerical quantities (such as explicit constants and L^AT_EX counters and length commands) and binary operators (the tokens '+', '-', '*', and '/' with their usual meaning) using the familiar infix notation; parentheses may be used to override the usual precedences (that multiplication/division have higher precedence than addition/subtraction).

Expressions must be properly typed. This means, e.g., that a dimen expression must be a sum of dimen terms: i.e., you cannot say '2cm+4' but '2cm+4pt' is valid.

In a dimen term, the dimension part must come first; the same holds for glue terms. Also, multiplication and division by non-integer quantities require a special syntax; see below.

Evaluation of subexpressions at the same level of precedence proceeds from left to right. Consider a dimen term such as “4cm*3*4”. First, the value of the factor 4cm is assigned to a dimen register, then this register is multiplied by 3 (using `\multiply`), and, finally, the register is multiplied by 4 (again using `\multiply`). This also explains why the dimension part (i.e., the part with the unit designation) must come first; T_EX simply doesn’t allow untyped constants to be assigned to a dimen register.

The `calc` package also allows multiplication and division by real numbers. However, a special syntax is required: you must use `\real{⟨decimal constant⟩}`² or `\ratio{⟨dimen expression⟩}{⟨dimen expression⟩}` to denote a real value to be used for multiplication/division. The first form has the obvious meaning, and the second form denotes the number obtained by dividing the value of the first expression by the value of the second expression.

A later addition to the package (in June 1998) allows an additional method of specifying a factor of type dimen by setting some text (in LR-mode) and measuring its dimensions: these are denoted as follows.

`\widthof{⟨text⟩} \heightof{⟨text⟩} \depthof{⟨text⟩}`

These calculate the natural sizes of the `⟨text⟩` in exactly the same way as is done for the commands `\settoheight` etc. on Page 216 of the manual [2]. In August 2005 the package was further extended to provide the command

`\totalheightof{⟨text⟩}`

This command does exactly what you’d expect from its name. Additionally the package also provides the command

`\settototalheight{⟨cmd⟩}{⟨text⟩}`

Note that there is a small difference in the usage of these two methods of accessing text dimensions. After `\settoheight{⟨text⟩}{Some text}` you can use:

`\setlength{⟨parskip⟩}{0.68\textwd}`

whereas using the more direct access to the width of the text requires the longer form for multiplication, thus:

`\setlength{⟨parskip⟩}{\widthof{Some text} * \real{0.68}}`

T_EX discards the stretch and shrink components of glue when glue is multiplied by a real number. So, for example,

`\setlength{⟨parskip⟩}{3pt plus 3pt * \real{1.5}}`

will set the paragraph separation to 4.5pt with no stretch or shrink. Incidentally, note how spaces can be used to enhance readability. When T_EX is scanning for a `⟨number⟩` etc. it is common to terminate the scanning with a space token or by inserting `\relax`. As of version 4.3 `calc` allows `\relax` tokens to appear in places where they would usually be used for terminating T_EX’s scanning. In short this is just before any of `+-*/` or at the end of the expression being evaluated.

²Actually, instead of `⟨decimal constant⟩`, the more general `⟨optional signs⟩⟨factor⟩` can be used. However, that doesn’t add any extra expressive power to the language of infix expressions.

When TeX performs arithmetic on integers, any fractional part of the result is discarded. For example,

```
\setcounter{x}{7/2}
\setcounter{y}{3*\real{1.6}}
\setcounter{z}{3*\real{1.7}}
```

will assign the value 3 to the counter `x`, the value 4 to `y`, and the value 5 to `z`. This truncation also applies to *intermediate* results in the sequential computation of a composite expression; thus, the following command

```
\setcounter{x}{3 * \real{1.6} * \real{1.7}}
```

will assign 6 to `x`.

As an example of the use of `\ratio`, consider the problem of scaling a figure to occupy the full width (i.e., `\textwidth`) of the body of a page. Assume that the original dimensions of the figure are given by the `dimen` (length) variables, `\Xsize` and `\Ysize`. The height of the scaled figure can then be expressed by

```
\setlength{\newYsize}{\Ysize*\ratio{\textwidth}{\Xsize}}
```

Another new feature introduced in August 2005 was max and min operations with associated macros

```
\maxof{<type expression>}{<type expression>}
\minof{<type expression>}{<type expression>}
```

When *type* is either `<glue>` or `<dimen>` these macros are allowed only as part of addition or subtraction but when *type* is `<integer>` they can also be used when multiplying and dividing. In the latter case they follow the same syntax rules as `\ratio` and `\real` which means they must come after the `*` or the `/`. Thus

```
\setcounter{x}{3*\maxof{4+5}{3*4}+\minof{2*\real{1.6}}{5-1}}
```

will assign $3 \times \max(9, 12) + \min(3, 4) = 39$ to `x`. Similarly

```
\setlength{\parindent}{%
\minof{3pt}{\parskip}*\real{1.5}*\maxof{2*\real{1.6}}{2-1}}
```

will assign $\min(13.5\text{pt}, 4.5\text{\parskip})$ to `\parindent`.

3 Formal syntax

The syntax is described by the following set of rules. Note that the definitions of `<number>`, `<dimen>`, `<glue>`, `<decimal constant>`, and `<plus or minus>` are as in Chapter 24 of The TeXbook [1]; and `<text>` is LR-mode material, as in the manual [2]. We use *type* as a meta-variable, standing for ‘integer’, ‘dimen’, and ‘glue’.³

$$\begin{array}{ll}
 \langle type \text{ expression} \rangle & \longrightarrow \langle type \text{ term} \rangle \quad | \quad \langle type \text{ expression} \rangle \\
 & \langle \text{plus or minus} \rangle \langle type \text{ term} \rangle \\
 \langle type \text{ term} \rangle & \longrightarrow \langle type \text{ term} \rangle \langle type \text{ scan stop} \rangle \quad | \quad \langle type \text{ factor} \rangle \\
 & | \quad \langle type \text{ term} \rangle \langle \text{multiply or divide} \rangle \langle \text{integer} \rangle \quad | \quad \langle type \text{ term} \rangle
 \end{array}$$

³This version of the `calc` package doesn’t support evaluation of `muglue` expressions.

$\langle \text{multiply or divide} \rangle \langle \text{real number} \rangle \quad | \quad \langle \text{type term} \rangle$
 $\langle \text{multiply or divide} \rangle \quad \langle \text{max or min integer} \rangle$
 $\langle \text{type scan stop} \rangle \quad \longrightarrow \quad \langle \text{empty} \rangle \quad | \quad \langle \text{optional space} \rangle \quad | \quad \backslash \text{relax}$
 $\langle \text{type factor} \rangle \quad \longrightarrow \quad \langle \text{type} \rangle \quad | \quad \langle \text{text dimen factor} \rangle$
 $\quad | \quad \langle \text{max or min type} \rangle \quad | \quad (_{12} \langle \text{type expression} \rangle)_{12}$
 $\langle \text{integer} \rangle \quad \longrightarrow \quad \langle \text{number} \rangle$
 $\langle \text{max or min type} \rangle \quad \longrightarrow \quad \langle \text{max or min command} \rangle \quad \{$
 $\quad \langle \text{type expression} \rangle \quad \} \quad \{ \langle \text{type expression} \rangle \quad \}$
 $\langle \text{max or min command} \rangle \quad \longrightarrow \quad \backslash \text{maxof} \quad | \quad \backslash \text{minof}$
 $\langle \text{text dimen factor} \rangle \quad \longrightarrow \quad \langle \text{text dimen command} \rangle \{ \langle \text{text} \rangle \}$
 $\langle \text{text dimen command} \rangle \quad \longrightarrow \quad \backslash \text{widthof} \quad | \quad \backslash \text{heightof}$
 $\quad | \quad \backslash \text{depthof} \quad | \quad \backslash \text{totalheightof}$
 $\langle \text{multiply or divide} \rangle \quad \longrightarrow \quad *_{12} \quad | \quad /_{12}$
 $\langle \text{real number} \rangle \quad \longrightarrow \quad \backslash \text{ratio} \{ \langle \text{dimen expression} \rangle \} \{ \langle \text{dimen expression} \rangle$
 $\quad \} \quad | \quad \backslash \text{real} \{ \langle \text{optional signs} \rangle \langle \text{decimal constant} \rangle \}$
 $\langle \text{plus or minus} \rangle \quad \longrightarrow \quad +_{12} \quad | \quad -_{12}$
 $\langle \text{decimal constant} \rangle \quad \longrightarrow \quad ._{12} \quad | \quad ,_{12} \quad | \quad \langle \text{digit} \rangle$
 $\quad \langle \text{decimal constant} \rangle \quad | \quad \langle \text{decimal constant} \rangle \langle \text{digit} \rangle$
 $\langle \text{digit} \rangle \quad \longrightarrow \quad 0_{12} \quad | \quad 1_{12} \quad | \quad 2_{12} \quad | \quad 3_{12} \quad | \quad 4_{12} \quad | \quad 5_{12}$
 $\quad | \quad 6_{12} \quad | \quad 7_{12} \quad | \quad 8_{12} \quad | \quad 9_{12}$
 $\langle \text{optional signs} \rangle \quad \longrightarrow \quad \langle \text{optional spaces} \rangle \quad | \quad \langle \text{optional signs} \rangle$
 $\quad \langle \text{plus or minus} \rangle \langle \text{optional spaces} \rangle$

Relying heavily on T_EX to do the underlying assignments, it is only natural for **calc** to simulate T_EX's parsing machinery for these quantities. Therefore it a) imposes the same restrictions on the catcode of syntax characters as T_EX and b) tries to expand its argument fully. a) means that implicit characters for the tokens $*_{12}$, $/_{12}$, $(_{12}$, and $)_{12}$ will not work⁴ but because of b), the expansion should allow you to use macros that expand to explicit syntax characters.

4 The evaluation scheme

In this section, we shall for simplicity consider only expressions containing '+' (addition) and '*' (multiplication) operators. It is trivial to add subtraction and division.

An expression E is a sum of terms: $T_1 + \dots + T_n$; a term is a product of factors: $F_1 * \dots * F_m$; a factor is either a simple numeric quantity f (like $\langle \text{number} \rangle$ as described in the T_EXbook), or a parenthesized expression (E').

Since the T_EX engine can only execute arithmetic operations in a machine-code-like manner, we have to find a way to translate the infix notation into this 'instruction set'.

⁴eT_EX also assumes these catcodes when parsing a `\numexpr`, `\dimexpr`, `\glueexpr`, or `\muglueexpr` and does not allow implicit characters.

Our goal is to design a translation scheme that translates X (an expression, a term, or a factor) into a sequence of $\text{T}_{\text{E}}\text{X}$ instructions that does the following [Invariance Property]: correctly evaluates X , leaves the result in a global register A (using a global assignment), and does not perform global assignments to the scratch register B ; moreover, the code sequence must be balanced with respect to $\text{T}_{\text{E}}\text{X}$ groups. We shall denote the code sequence corresponding to X by $\llbracket X \rrbracket$.

In the replacement code specified below, we use the following conventions:

- A and B denote registers; all assignments to A will be global, and all assignments to B will be local.
- “ \Leftarrow ” means global assignment to the register on the lhs.
- “ \leftarrow ” means local assignment to the register on the lhs.
- “ $\hookrightarrow_{[C]}$ ” means “save the code C until the current group (scope) ends, then execute it.” This corresponds to the $\text{T}_{\text{E}}\text{X}$ -primitive `\aftergroup`.
- “{” denotes the start of a new group, and “}” denotes the end of a group.

Let us consider an expression $T_1 + T_2 + \dots + T_n$. Assuming that $\llbracket T_k \rrbracket$ ($1 \leq k \leq n$) attains the stated goal, the following code clearly attains the stated goal for their sum:

$$\begin{aligned} \llbracket T_1 + T_2 + \dots + T_n \rrbracket \implies & \{ \llbracket T_1 \rrbracket \} B \leftarrow A \quad \{ \llbracket T_2 \rrbracket \} B \leftarrow B + A \\ & \dots \quad \{ \llbracket T_n \rrbracket \} B \leftarrow B + A \quad A \Leftarrow B \end{aligned}$$

Note the extra level of grouping enclosing each of $\llbracket T_1 \rrbracket$, $\llbracket T_2 \rrbracket$, \dots , $\llbracket T_n \rrbracket$. This will ensure that register B , used to compute the sum of the terms, is not clobbered by the intermediate computations of the individual terms. Actually, the group enclosing $\llbracket T_1 \rrbracket$ is unnecessary, but it turns out to be simpler if all terms are treated the same way.

The code sequence “ $\{ \llbracket T_2 \rrbracket \} B \leftarrow B + A$ ” can be translated into the following equivalent code sequence: “ $\{ \hookrightarrow_{[B \leftarrow B + A]} \llbracket T_2 \rrbracket \}$ ”. This observation turns out to be the key to the implementation: The “ $\hookrightarrow_{[B \leftarrow B + A]}$ ” is generated *before* T_2 is translated, at the same time as the ‘+’ operator between T_1 and T_2 is seen.

Now, the specification of the translation scheme is straightforward:

$$\begin{aligned} \llbracket f \rrbracket & \implies A \Leftarrow f \\ \llbracket (E') \rrbracket & \implies \llbracket E' \rrbracket \\ \llbracket T_1 + T_2 + \dots + T_n \rrbracket & \implies \{ \hookrightarrow_{[B \leftarrow A]} \llbracket T_1 \rrbracket \} \quad \{ \hookrightarrow_{[B \leftarrow B + A]} \llbracket T_2 \rrbracket \} \\ & \quad \dots \quad \{ \hookrightarrow_{[B \leftarrow B + A]} \llbracket T_n \rrbracket \} \quad A \Leftarrow B \\ \llbracket F_1 * F_2 * \dots * F_m \rrbracket & \implies \{ \hookrightarrow_{[B \leftarrow A]} \llbracket F_1 \rrbracket \} \quad \{ \hookrightarrow_{[B \leftarrow B * A]} \llbracket F_2 \rrbracket \} \\ & \quad \dots \quad \{ \hookrightarrow_{[B \leftarrow B * A]} \llbracket F_m \rrbracket \} \quad A \Leftarrow B \end{aligned}$$

By structural induction, it is easily seen that the stated property is attained.

By inspection of this translation scheme, we see that we have to generate the following code:

- we must generate “ $\{ \hookrightarrow_{[B \leftarrow A]} \{ \hookrightarrow_{[B \leftarrow A]} \}$ ” at the left border of an expression (i.e., for each left parenthesis and the implicit left parenthesis at the beginning of the whole expression);

- we must generate “ $\}A \leftarrow B\}A \leftarrow B$ ” at the right border of an expression (i.e., each right parenthesis and the implicit right parenthesis at the end of the full expression);
- ‘*’ is replaced by “ $\}\{\hookrightarrow[B \leftarrow B * A]$ ”;
- ‘+’ is replaced by “ $\}A \leftarrow B\}\{\hookrightarrow[B \leftarrow B + A]\{\hookrightarrow[B \leftarrow A]$ ”;
- when we see (expect) a numeric quantity, we insert the assignment code “ $A \leftarrow$ ” in front of the quantity and let \TeX parse it.

5 Implementation

For brevity define

$$\langle \text{numeric} \rangle \longrightarrow \langle \text{number} \rangle \mid \langle \text{dimen} \rangle \mid \langle \text{glue} \rangle \mid \langle \text{muglue} \rangle$$

So far we have ignored the question of how to determine the type of register to be used in the code. However, it is easy to see that (1) ‘*’ always initiates an $\langle \text{integer factor} \rangle$, (2) all $\langle \text{numeric} \rangle$ s in an expression, except those which are part of an $\langle \text{integer factor} \rangle$, are of the same type as the whole expression, and all $\langle \text{numeric} \rangle$ s in an $\langle \text{integer factor} \rangle$ are $\langle \text{number} \rangle$ s.

We have to ensure that A and B always have an appropriate type for the $\langle \text{numeric} \rangle$ s they manipulate. We can achieve this by having an instance of A and B for each type. Initially, A and B refer to registers of the proper type for the whole expression. When an $\langle \text{integer factor} \rangle$ is expected, we must change A and B to refer to integer type registers. We can accomplish this by including instructions to change the type of A and B to integer type as part of the replacement code for ‘*’; if we append such instructions to the replacement code described above, we also ensure that the type change is local (provided that the type-changing instructions only have local effect). However, note that the instance of A referred to in $\hookrightarrow[B \leftarrow B * A]$ is the integer instance of A .

We shall use `\begingroup` and `\endgroup` for the open-group and close-group characters. This avoids problems with spacing in math (as pointed out to us by Frank Mittelbach).

5.1 Getting started

Now we have enough insight to do the actual implementation in \TeX . First, we announce the macro package.⁵

```
1 \*package
2 %\NeedsTeXFormat{LaTeX2e}
3 %\ProvidesPackage{calc}[\filedate\space\fileversion]
```

5.2 Assignment macros

`\calc@assign@generic` The `\calc@assign@generic` macro takes four arguments: (1 and 2) the registers to be used for global and local manipulations, respectively; (3) the lvalue part; (4) the expression to be evaluated.

⁵Code moved to top of file

The third argument (the lvalue) will be used as a prefix to a register that contains the value of the specified expression (the fourth argument).

In general, an lvalue is anything that may be followed by a variable of the appropriate type. As an example, `\linepenalty` and `\global\advance\linepenalty` may both be followed by an \langle integer variable \rangle .

The macros described below refer to the registers by the names `\calc@A` and `\calc@B`; this is accomplished by `\let`-assignments.

As discovered in Section 4, we have to generate code as if the expression is parenthesized. As described below, `\calc@open` is the macro that replaces a left parenthesis by its corresponding TeX code sequence. When the scanning process sees the exclamation point, it generates an `\endgroup` and stops. As we recall from Section 4, the correct expansion of a right parenthesis is “ $\}A \leftarrow B\}A \leftarrow B$ ”. The remaining tokens of this expansion are inserted explicitly, except that the last assignment has been replaced by the lvalue part (i.e., argument #3 of `\calc@assign@generic`) followed by `\calc@B`.

```
4 \def\calc@assign@generic#1#2#3#4{\let\calc@A#1\let\calc@B#2%
5   \calc@open(#4!%
6   \global\calc@A\calc@B\endgroup#3\calc@B}
```

`\calc@assign@count` We need three instances of the `\calc@assign@generic` macro, corresponding to the types \langle integer \rangle , \langle dimen \rangle , and \langle glue \rangle .

```
\calc@assign@skip 7 \def\calc@assign@count{\calc@assign@generic\calc@Acount\calc@Bcount}
8 \def\calc@assign@dimen{\calc@assign@generic\calc@Adimen\calc@Bdimen}
9 \def\calc@assign@skip{\calc@assign@generic\calc@Askip\calc@Bskip}
```

These macros each refer to two registers, one to be used globally and one to be used locally. We must allocate these registers.

```
10 \newcount\calc@Acount   \newcount\calc@Bcount
11 \newdimen\calc@Adimen   \newdimen\calc@Bdimen
12 \newskip\calc@Askip     \newskip\calc@Bskip
```

5.3 The L^AT_EX interface

`\setcounter` As promised, we redefine the following standard L^AT_EX commands: `\setcounter`, `\addtocounter`, `\setlength`, and `\addtolength`.

```
\steptocounter 13 \def\setcounter#1#2{\@ifundefined{c@#1}{\@nocounterr{#1}}%
\setlength      14   {\calc@assign@count{\global\csname c@#1\endcsname}{#2}}%
\addtolength    15 \def\addtocounter#1#2{\@ifundefined{c@#1}{\@nocounterr{#1}}%
16   {\calc@assign@count{\global\advance\csname c@#1\endcsname}{#2}}}%
17
```

We also fix `\stepcounter` to not go through the whole calc process.

```
17 \def\stepcounter#1{\@ifundefined{c@#1}%
18   {\@nocounterr{#1}}%
19   {\global\advance\csname c@#1\endcsname \@ne
20   \begingroup
21     \let\@elt\@stpelt \csname cl@#1\endcsname
22   \endgroup}}%
```

If the `amstext` package is loaded we must add the `\iffirstchoice@` switch as well. We patch the commands this way since it's good practice when we know how many arguments they take.


```

23 \AtBeginDocument{%
24   \ifpackageloaded{amstext}{%
25     \def\addtocounter#1#2{\iffirstchoice@
26       \ifundefined{c@#1}{\@nocounterr{#1}}%
27       {\calc@assign@count{\global\advance\csname c@#1\endcsname}{#2}}%
28       \fi}%
29     \def\stepcounter#1{\iffirstchoice@
30       \ifundefined{c@#1}%
31       {\@nocounterr{#1}}%
32       {\global\advance\csname c@#1\endcsname \one
33         \begingroup
34           \let\elt\stpelt \csname cl@#1\endcsname
35           \endgroup}%
36       \fi}%
37   }%
38 }

39 \DeclareRobustCommand\setlength{\calc@assign@skip}
40 \DeclareRobustCommand\addtolength[1]{\calc@assign@skip{\advance#1}}

```

(\setlength and \addtolength are robust according to [2].)

5.4 The scanner

We evaluate expressions by explicit scanning of characters. We do not rely on active characters for this.

The scanner consists of two parts, `\calc@pre@scan` and `\calc@post@scan`; `\calc@pre@scan` consumes left parentheses, and `\calc@post@scan` consumes binary operator, `\real`, `\ratio`, and right parenthesis tokens.

`\calc@pre@scan` Note that this is called at least once on every use of `calc` processing, even when `\@calc@pre@scan` none of the extended syntax is present; it therefore needs to be made very efficient.

It reads the initial part of expressions, until some `<text dimen factor>` or `<numeric>` is seen; in fact, anything not explicitly recognized here is taken to be a `<numeric>` of some sort as this allows unary `+` and unary `-` to be treated easily and correctly⁶ but means that anything illegal will simply generate a T_EX-level error, often a reasonably comprehensible one!

The `\romannumeral-‘\a` part is a little trick which forces expansion in case `#1` is a normal macro, something that occurs from time to time. A conditional test inside will possibly leave a trailing `\fi` but this remnant is removed later when `\calc@post@scan` performs the same trick.

The many `\expandafters` are needed to efficiently end the nested conditionals so that `\calc@textsize` and `\calc@maxmin@addsub` can process their argument.

```

41 \def\calc@pre@scan#1{%
42   \expandafter\@calc@pre@scan\romannumeral-‘\a#1}
43 \def\@calc@pre@scan#1{%
44   \ifx(#1%
45     \expandafter\calc@open
46   \else
47     \ifx\widthof#1%
48       \expandafter\expandafter\expandafter\calc@textsize

```

⁶In the few contexts where signs are allowed: this could, I think, be extended (CAR).

```

49   \else
50     \ifx\maxof#1%
51       \expandafter\expandafter\expandafter\expandafter
52       \expandafter\expandafter\expandafter\calc@maxmin@addsub
53     \else
54       \calc@numeric% no \expandafter needed for this one.
55     \fi
56   \fi
57 \fi
58 #1}

```

`\calc@open` `\calc@open` is used when there is a left parenthesis right ahead. This parenthesis `\calc@initB` is replaced by T_EX code corresponding to the code sequence “ $\{\hookrightarrow[B\leftarrow A]\{\hookrightarrow[B\leftarrow A]\}$ ” derived in Section 4. Finally, `\calc@pre@scan` is called again.

```

59 \def\calc@open{\begingroup\aftergroup\calc@initB
60   \begingroup\aftergroup\calc@initB
61   \calc@pre@scan}
62 \def\calc@initB{\calc@B\calc@A}

```

`\calc@numeric` `\calc@numeric` assigns the following value to `\calc@A` and then transfers control to `\calc@post@scan`.

```

63 \def\calc@numeric{\afterassignment\calc@post@scan \global\calc@A}

```

`\widthof` These do not need any particular definition when they are scanned so, for efficiency and robustness, we make them all equivalent to the same harmless (I hope) `\heightof` unexpandable command.⁷ Thus the test in `\@calc@pre@scan` finds any of them.
`\depthof`
`\totalheightof` As we have to check for these commands explicitly we must ensure that our definition wins. Using `\newcommand` gives an error when loading `calc` and may be mildly surprising. This should be a little more informative.

```

64 \@for\reserved@a:=widthof,heightof,depthof,totalheightof,maxof,minof\do
65 {\@ifundefined{\reserved@a}\{}{\%
66   \PackageError{calc}{%
67     The\space calc\space package\space reserves\space the\space
68     command\space name\space ‘\@backslashchar\reserved@a’\MessageBreak
69     but\space it\space has\space already\space been\space defined\space
70     with\space the\space meaning\space \MessageBreak
71     ‘\expandafter\meaning\csname\reserved@a\endcsname’.\MessageBreak
72     This\space original\space definition\space will\space be\space lost}%
73     {If\space you\space need\space a\space command\space with\space
74     this\space definition,\space you\space must\space use\space a\space
75     different\space name.}}}%
76 }
77 \let\widthof\ignorespaces
78 \let\heightof\ignorespaces
79 \let\depthof\ignorespaces
80 \let\totalheightof\ignorespaces

```

`\calc@textsize` The presence of the above four commands invokes this code, where we must distinguish them from each other. This implementation is somewhat optimized by using low-level code from the commands `\settowidth`, etc.⁸

⁷If this level of safety is not needed then the code can be sped up: CAR.

⁸It is based on suggestions by Donald Arseneau and David Carlisle.

Within the text argument we must restore the normal meanings of the four user-level commands since arbitrary material can appear in here, including further uses of `calc`.

```

81 \def\calc@textsize #1#2{%
82   \begingroup
83   \let\widthof\wd
84   \let\heightof\ht
85   \let\depthof\dp
86   \def\totalheightof{\ht\dp}%

```

We must expand the argument one level if it's `\totalheightof` and it doesn't hurt the other three.

```

87   \expandafter\@settodim\expandafter{#1}%
88   {\global\calc@A}%
89   {%
90     \let\widthof\ignorespaces
91     \let\heightof\ignorespaces
92     \let\depthof\ignorespaces
93     \let\totalheightof\ignorespaces
94     #2}%
95   \endgroup
96   \calc@post@scan}

```

`\calc@post@scan` The macro `\calc@post@scan` is called right after a value has been read. At this point, a binary operator, a sequence of right parentheses, an optional `\relax`, and the end-of-expression mark (`'!`) is allowed.⁹ Depending on our findings, we call a suitable macro to generate the corresponding TeX code (except when we detect the end-of-expression marker: then scanning ends, and control is returned to `\calc@assign@generic`).

This macro may be optimized by selecting a different order of `\ifx`-tests. The test for `'!` (end-of-expression) is placed first as it will always be performed: this is the only test to be performed if the expression consists of a single `<numeric>`. This ensures that documents that do not use the extra expressive power provided by the `calc` package only suffer a minimum slowdown in processing time.

```

97 \def\calc@post@scan#1{%
98   \expandafter\@calc@post@scan\romannumeral-'\a#1}
99 \def\@calc@post@scan#1{%
100   \ifx#1!\let\calc@next\endgroup \else
101     \ifx#1+\let\calc@next\calc@add \else
102       \ifx#1-\let\calc@next\calc@subtract \else
103         \ifx#1*\let\calc@next\calc@multiply \else
104           \ifx#1/\let\calc@next\calc@dividex \else
105             \ifx#1)\let\calc@next\calc@close \else
106               \ifx#1\relax\let\calc@next\calc@post@scan \else
107                 \def\calc@next{\calc@error#1}%
108             \fi
109           \fi
110         \fi
111       \fi
112     \fi
113   \fi

```

⁹Is `!` a good choice, CAR?

```

114 \fi
115 \calc@next}

```

`\calc@add` The replacement code for the binary operators ‘+’ and ‘-’ follows a common pattern; the only difference is the token that is stored away by `\aftergroup`. After `\calc@generic@add` this replacement code, control is transferred to `\calc@pre@scan`.

```

\calc@addAtoB 116 \def\calc@add{\calc@generic@add\calc@addAtoB}
\calc@subtractAfromB 117 \def\calc@subtract{\calc@generic@add\calc@subtractAfromB}
118 \def\calc@generic@add#1{\endgroup\global\calc@A\calc@B\endgroup
119 \begingroup\aftergroup#1\begingroup\aftergroup\calc@initB
120 \calc@pre@scan}
121 \def\calc@addAtoB{\advance\calc@B\calc@A}
122 \def\calc@subtractAfromB{\advance\calc@B-\calc@A}

```

`\real` The multiplicative operators, ‘*’ and ‘/’, may be followed by a `\real`, `\ratio`, `\minof`, or `\maxof` token. The last two of these control sequences are defined by `calc` as they are needed by the scanner for addition or subtraction while the first two are not defined (at least not by the `calc` package); this, unfortunately, leaves them highly non-robust. We therefore equate them to `\relax` but only if they have not already been defined¹⁰ (by some other package: dangerous but possible!); this will also make them appear to be undefined to a L^AT_EX user (also possibly dangerous).

```

123 \ifx\real\@undefined\let\real\relax\fi
124 \ifx\ratio\@undefined\let\ratio\relax\fi

```

In order to test for `\real` or `\ratio`, we define these two.¹¹

```

125 \def\calc@ratio@x{\ratio}
126 \def\calc@real@x{\real}

```

`\calc@multiplyx` Test which operator followed * or /. If none followed it’s just a standard multiplication or division.

```

127 \def\calc@multiplyx#1{\def\calc@tmp{#1}%
128 \ifx\calc@tmp\calc@ratio@x \let\calc@next\calc@ratio@multiply \else
129 \ifx\calc@tmp\calc@real@x \let\calc@next\calc@real@multiply \else
130 \ifx\maxof#1\let\calc@next\calc@maxmin@multiply \else
131 \let\calc@next\calc@multiply
132 \fi
133 \fi
134 \fi
135 \calc@next#1}
136 \def\calc@dividex#1{\def\calc@tmp{#1}%
137 \ifx\calc@tmp\calc@ratio@x \let\calc@next\calc@ratio@divide \else
138 \ifx\calc@tmp\calc@real@x \let\calc@next\calc@real@divide \else
139 \ifx\maxof#1\let\calc@next\calc@maxmin@divide \else
140 \let\calc@next\calc@divide
141 \fi
142 \fi
143 \fi
144 \calc@next#1}

```

¹⁰Suggested code from David Carlisle.

¹¹May not need the extra names, CAR?

`\calc@multiply` The binary operators ‘`*`’ and ‘`/`’ also insert code as determined above. Moreover,
`\calc@divide` the meaning of `\calc@A` and `\calc@B` is changed as factors following a multiplica-
`\calc@generic@multiply` tion and division operator always have integer type; the original meaning of these
`\calc@multiplyBbyA` macros will be restored when the factor has been read and evaluated.

```

\calc@divideBbyA 145 \def\calc@multiply{\calc@generic@multiply\calc@multiplyBbyA}
146 \def\calc@divide{\calc@generic@multiply\calc@divideBbyA}
147 \def\calc@generic@multiply#1{\endgroup\beginingroup
148   \let\calc@A\calc@Acount \let\calc@B\calc@Bcount
149   \aftergroup#1\calc@pre@scan}
150 \def\calc@multiplyBbyA{\multiply\calc@B\calc@Acount}
151 \def\calc@divideBbyA{\divide\calc@B\calc@Acount}

```

Since the value to use in the multiplication/division operation is stored in the `\calc@Acount` register, the `\calc@multiplyBbyA` and `\calc@divideBbyA` macros use this register.

`\calc@close` `\calc@close` generates code for a right parenthesis (which was derived to be “ $A \leftarrow B$ ” in Section 4). After this code, the control is returned to `\calc@post@scan` in order to look for another right parenthesis or a binary operator.

```

152 \def\calc@close
153   {\endgroup\global\calc@A\calc@B
154   \endgroup\global\calc@A\calc@B
155   \calc@post@scan}

```

5.5 Calculating a ratio

`\calc@ratio@multiply` When `\calc@post@scan` encounters a `\ratio` control sequence, it hands control to
`\calc@ratio@divide` one of the macros `\calc@ratio@multiply` and `\calc@ratio@divide`, depending on the preceding character. Those macros both forward the control to the macro `\calc@ratio@evaluate`, which performs two steps: (1) it calculates the ratio, which is saved in the global macro token `\calc@the@ratio`; (2) it makes sure that the value of `\calc@B` will be multiplied by the ratio as soon as the current group ends.

The following macros call `\calc@ratio@evaluate` which multiplies `\calc@B` by the ratio, but `\calc@ratio@divide` flips the arguments so that the ‘opposite’ fraction is actually evaluated.

```

156 \def\calc@ratio@multiply\ratio{\calc@ratio@evaluate}
157 \def\calc@ratio@divide\ratio#1#2{\calc@ratio@evaluate{#2}{#1}}

```

`\calc@Ccount` We shall need two registers for temporary usage in the calculations. We can save
`\calc@numerator` one register since we can reuse `\calc@Bcount`.

```

\calc@denominator 158 \newcount\calc@Ccount
159 \let\calc@numerator=\calc@Bcount
160 \let\calc@denominator=\calc@Ccount

```

`\calc@ratio@evaluate` Here is the macro that handles the actual evaluation of ratios. The procedure is this: First, the two expressions are evaluated and coerced to integers. The whole procedure is enclosed in a group to be able to use the registers `\calc@numerator` and `\calc@denominator` for temporary manipulations.

```

161 \def\calc@ratio@evaluate#1#2{%
162   \endgroup\beginingroup

```

```

163 \calc@assign@dimen\calc@numerator{#1}%
164 \calc@assign@dimen\calc@denominator{#2}%

```

Here we calculate the ratio. First, we check for negative numerator and/or denominator; note that T_EX interprets two minus signs the same as a plus sign. Then, we calculate the integer part. The minus sign(s), the integer part, and a decimal point form the initial expansion of the `\calc@the@ratio` macro.

```

165 \gdef\calc@the@ratio{}%
166 \ifnum\calc@numerator<0 \calc@numerator-\calc@numerator
167 \gdef\calc@the@ratio{-}%
168 \fi
169 \ifnum\calc@denominator<0 \calc@denominator-\calc@denominator
170 \xdef\calc@the@ratio{\calc@the@ratio-}%
171 \fi
172 \calc@Acount\calc@numerator
173 \divide\calc@Acount\calc@denominator
174 \xdef\calc@the@ratio{\calc@the@ratio\number\calc@Acount.}%

```

Now we generate the digits after the decimal point, one at a time. When T_EX scans these digits (in the actual multiplication operation), it forms a fixed-point number with 16 bits for the fractional part. We hope that six digits is sufficient, even though the last digit may not be rounded correctly.

```

175 \calc@next@digit \calc@next@digit \calc@next@digit
176 \calc@next@digit \calc@next@digit \calc@next@digit
177 \endgroup

```

Now we have the ratio represented (as the expansion of the global macro `\calc@the@ratio`) in the syntax $\langle \text{decimal constant} \rangle$ [1, page 270]. This is fed to `\calc@multiply@by@real` that will perform the actual multiplication. It is important that the multiplication takes place at the correct grouping level so that the correct instance of the *B* register will be used. Also note that we do not need the `\aftergroup` mechanism in this case.

```

178 \calc@multiply@by@real\calc@the@ratio
179 \begingroup
180 \calc@post@scan}

```

The `\begingroup` inserted before the `\calc@post@scan` will be matched by the `\endgroup` generated as part of the replacement of a subsequent binary operator or right parenthesis.

`\calc@next@digit`

```

181 \def\calc@next@digit{%
182 \multiply\calc@Acount\calc@denominator
183 \advance\calc@numerator -\calc@Acount
184 \multiply\calc@numerator 10
185 \calc@Acount\calc@numerator
186 \divide\calc@Acount\calc@denominator
187 \xdef\calc@the@ratio{\calc@the@ratio\number\calc@Acount}}

```

`\calc@multiply@by@real` In the following code, it is important that we first assign the result to a *dimen* register. Otherwise, T_EX won't allow us to multiply with a real number.

```

188 \def\calc@multiply@by@real#1{\calc@Bdimen #1\calc@B \calc@B\calc@Bdimen}

```

(Note that this code wouldn't work if `\calc@B` were a muglue register. This is the real reason why the `calc` package doesn't support muglue expressions. To support muglue expressions in full, the `\calc@multiply@by@real` macro must use a muglue register instead of `\calc@Bdimen` when `\calc@B` is a muglue register; otherwise, a `dimen` register should be used. Since integer expressions can appear as part of a muglue expression, it would be necessary to determine the correct register to use each time a multiplication is made.)

5.6 Multiplication by real numbers

`\calc@real@multiply` This is similar to the `\calc@ratio@evaluate` macro above, except that it is considerably simplified since we don't need to calculate the factor explicitly.

```
189 \def\calc@real@multiply\real#1{\endgroup
190   \calc@multiply@by@real{#1}\begingroup
191   \calc@post@scan}
192 \def\calc@real@divide\real#1{\calc@ratio@evaluate{1pt}{#1pt}}
```

5.7 max and min operations

`\maxof` With version 4.2, the max and min operators were added to `calc`. The user functions for them are `\maxof` and `\minof` respectively. These macros are internally similar to `\widthof` etc. in that they are unexpandable and easily recognizable by the scanner.

```
193 \let\maxof\@@italiccorr
194 \let\minof\@@italiccorr
```

`\calc@Cskip` The max and min operations take two arguments so we need an extra `<skip>` register. We also add a switch for determining when to perform a `<skip>` or a `<count>` assignment.

```
195 \newskip\calc@Cskip
196 \newif\ifcalc@count@
```

`\calc@maxmin@addsub` When doing addition or subtraction with a max or min operator, we first check if `\calc@A` is a `<count>` register or not and then set the switch. Then call the real function which sets `\calc@A` to the desired value and continue as usual with `\calc@post@scan`.

```
197 \def\calc@maxmin@addsub#1#2#3{\begingroup
198   \ifx\calc@A\calc@Acount%
199     \calc@count@true
200   \else
201     \calc@count@false
202   \fi
203   \calc@maxmin@generic#1{#2}{#3}%
204 \endgroup
205 \calc@post@scan
206 }
```

Check the switch and do either `<count>` or `<skip>` assignments. Note that `\maxof` and `\minof` are not set to `>` and `<` until after the assignments, which ensures we can nest them without problems. Then set `\calc@A` to the correct one.

```
207 \def\calc@maxmin@generic#1#2#3{%
208   \begingroup
```

```

209 \ifcalc@count@
210 \calc@assign@count\calc@Ccount{#2}%
211 \calc@assign@count\calc@Bcount{#3}%
212 \def\minof{<}\def\maxof{>}%
213 \global\calc@A\ifnum\calc@Ccount#1\calc@Bcount
214 \calc@Ccount\else\calc@Bcount\fi
215 \else
216 \calc@assign@skip\calc@Cskip{#2}%
217 \calc@assign@skip\calc@Bskip{#3}%
218 \def\minof{<}\def\maxof{>}%
219 \global\calc@A\ifdim\calc@Cskip#1\calc@Bskip
220 \calc@Cskip\else\calc@Bskip\fi
221 \fi
222 \endgroup
223 }

```

`\calc@maxmin@divmul` When doing division or multiplication we must be using `<count>` registers so we
`\calc@maxmin@multiply` set the switch. Other than that it is almost business as usual when multiplying or
`\calc@maxmin@divide` dividing. #1 is the instruction to either multiply or divide `\calc@B` by `\calc@A`,
#2 is either `\maxof` or `\minof` which is waiting in the input stream and #3 and #4
are the calc expressions. We end it all as usual by calling `\calc@post@scan`.

```

224 \def\calc@maxmin@divmul#1#2#3#4{%
225 \endgroup\begin group
226 \calc@count@true
227 \aftergroup#1%
228 \calc@maxmin@generic#2{#3}{#4}%
229 \endgroup\begin group
230 \calc@post@scan
231 }

```

The two functions called when seeing a `*` or a `/`.

```

232 \def\calc@maxmin@multiply{\calc@maxmin@divmul\calc@multiplyBbyA}
233 \def\calc@maxmin@divide {\calc@maxmin@divmul\calc@divideBbyA}

```

6 Reporting errors

`\calc@error` If `\calc@post@scan` reads a character that is neither `'+'`, `'-'`, `'*'`, `'/'`, nor `'>'`, an
error has occurred, and this is reported to the user. Violations in the syntax of
`<numeric>`s will be detected and reported by `TEX`.

```

234 \def\calc@error#1{%
235 \PackageError{calc}%
236 {'#1' invalid at this point}%
237 {I expected to see one of: + - * / >}}

```

7 Other additions

`\@settodim` The kernel macro `\@settodim` is changed so that it runs through a list containing
`\setttotalheight` `\ht`, `\wd`, and `\dp` and then advances the length one step at a time. We just have
to use a scratch register in case the user decides to put in a `\global` prefix on the
length register. A search on the internet confirmed that some people do that kind
of thing.


```

238 \def\@settodim#1#2#3{%
239   \setbox\@tempboxa\hbox
240     {\SuspendTagging{\@settodim}#3\ResumeTagging{\@settodim}}}%
241   \dimen@ii=\z@
242   \tfr\reserved@a #1\do{%
243     \advance\dimen@ii\reserved@a\@tempboxa}%
244   #2=\dimen@ii
245   \setbox\@tempboxa\box\voidb@x}

```

Now the user level macro is straightforward.

```

246 \def\settototalheight{\@settodim{\ht\dp}}

```

That's the end of the package.

```

247 \endpackage

```

References

- [1] D. E. KNUTH. *The T_EXbook* (Computers & Typesetting Volume A). Addison-Wesley, Reading, Massachusetts, 1986.
- [2] L. LAMPORT. *L_AT_EX, A Document Preparation System*. Addison-Wesley, Reading, Massachusetts, Second edition 1994/1985.

Change History

v4.0d		v4.2
General: Contributed to tools distribution	1	\@calc@post@scan: Added macro and force expansion 11
\calc@error: Use \PackageError for error messages (DPC) . . .	16	\@calc@pre@scan: Added \maxof and \minof operations 9
v4.0e		Added macro and force expansion 9
\calc@error: typo fixed	16	\@settodim: Changed kernel macro 16
v4.1a		\addtocounter: Fix to make \addtocounter work with amstext 8
General: Added text sizes: CAR . .	1	\calc@assign@generic: Removed a few redundant \expandafers 7
Attempt to make user-syntax robust: CAR	1	\calc@dividx: Added max and min operations 12
\@calc@pre@scan: Added code for text sizes: CAR	9	\calc@maxmin@divide: Macros added 16
\calc@error: Improved, I hope, error message: CAR	16	\calc@maxmin@generic: Macros added 15
\calc@real@x: Added macro set-ups to make them robust but undefined: CAR	12	\calc@multiplyx: Added max and min operations 12
\calc@textsize: Added macro: CAR	10	\calc@textsize: Extended macro with \totalheightof 10
\depthof: Added macros: CAR . .	10	\minof: Added macros 15
v4.1b		
\@calc@pre@scan: Correction to ifx true case	9	

	\setttotalheight: Added macro	16	terminating \relax tokens and	
	\steptocounter: Avoid redundant		avoid extra error message from	
	processing. PR/3795	8	\calc@next	11
	\totalheightof: Added			
	informative message for		v4.3a	
	reserved macros	10	\@settodim: Suspend Tagging	16
	Added macro	10		
v4.3			v4.3b	
	\@calc@post@scan: Discard		\addtolength: Delay amstext test	8