

xfakebold, v. 0.10
using bold characters with
pdflatex, lualatex or xelatex

Herbert Voß

November 21, 2023

Contents

1 T_EX-engines	2
2 How does it work?	2
3 Optional package argument	2
4 The macros	2
5 The example code	3
5.1 Default setting	3
6 Loading the package with another value	3
7 Using the optional argument of the macro	4

Abstract

The package fakes a vector font with outline characters by the text render of PDF. It writes directly into the pdf output with `\pdfliteral` and uses the `colorstack` package `pdfrender` to allow boldness with a pagebreak inside the bold part. The package defines two macros which can be used in text and in math mode. However, for the text mode one should use the bold version of the text font which should be available in most cases. This is different to the math mode where only some free math fonts provide a bold version.


Thanks to: Yukai Chou; Martin Münch; Heiko Oberdiek; Scott Pakin, Will Robertson; Yusuke Terada;

1 T_EX-engines

With X_{EL}A_TE_X you do not really need this package, because you can use the optional argument AutoFakeBold from package fontspec or unicode-math which does the same internally. For Lu_AT_EX the option AutoFakeBold is only supported by unicode-math for math typesetting. For pdfL_AT_EX this package can be used for text and math.

2 How does it work?

PDF knows different text render modes for outline fonts.



In mode 0 the character is filled but without drawing its outline which can be seen when printing in mode 1, where the linewidth of the outline is the smallest one which the system allows. Setting the linewidth to 0.3 bp, which is nearly the same as 0.3 pt, the linewidth of the outline increases. In mode 2 the character is printed with filling *and* drawing the outline, which is mode 0 and 1 together. The reason why the character is bold by default. Increasing the linewidth makes it more bold.

3 Optional package argument

The only package option is bold which is preset by 0.3, which is the linewidth of the outlines of the characters.

```
\usepackage[bold=0.6]{xfakebold}
```

makes the characters more bold.

4 The macros

```
\setBold[<optional value>]  
\unsetBold
```

Without using the optional argument the default setting is used.

5 The example code

The following examples use the value for π , defined in L^AT_EX3 as `\c_pi_fp`. To get rid of the L3-syntax we define a new variable:

```
\ExplSyntaxOn
\let\PI\c_pi_fp
\ExplSyntaxOff
```

5.1 Default setting

```
\documentclass{article}
\usepackage{xfakebold,xfp}
\begin{document}
An example:
$\pi^{\pi}=\fpeval{\PI^{\PI}}$ and
$\displaystyle\int\limits_1^{\infty}\frac{1}{x^2}\mathrm{d}x=1$ 

\setBold\noindent
An example:
$\pi^{\pi}=\fpeval{\PI^{\PI}}$ and
$\displaystyle\int\limits_1^{\infty}\frac{1}{x^2}\mathrm{d}x=1$ 

\unsetBold\noindent
An example:
$\pi^{\pi}=\fpeval{\PI^{\PI}}$ and
$\displaystyle\int\limits_1^{\infty}\frac{1}{x^2}\mathrm{d}x=1$ 
\end{document}
```

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

6 Loading the package with another value

```
\documentclass{article}
\usepackage[bold=1]{xfakebold}
\usepackage{xfp}
\begin{document}
An example:
$\pi^{\pi}=\fpeval{\PI^{\PI}}$ and
$\displaystyle\int\limits_1^{\infty}\frac{1}{x^2}\mathrm{d}x=1$ 

\setBold\noindent
An example:
$\pi^{\pi}=\fpeval{\PI^{\PI}}$ and
$\displaystyle\int\limits_1^{\infty}\frac{1}{x^2}\mathrm{d}x=1$ 

\unsetBold\noindent
An example:
$\pi^{\pi}=\fpeval{\PI^{\PI}}$ and
$\displaystyle\int\limits_1^{\infty}\frac{1}{x^2}\mathrm{d}x=1$ 
\end{document}
```

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

7 Using the optional argument of the macro

```
\documentclass{article}
\usepackage{xfakebold,xfp}
\begin{document}
\setBold[0.01]\noindent
An example:
$\pi^\pi=\fpeval{\PI^\PI}$ and
\$displaystyle\int\limits_1^\infty\frac{1}{x^2}\symup dx=1$
```

```
\setBold[0.2]\noindent
An example:
$\pi^\pi=\fpeval{\PI^\PI}$ and
\$displaystyle\int\limits_1^\infty\frac{1}{x^2}\symup dx=1$
```

```
\setBold[0.6]\noindent
An example:
$\pi^\pi=\fpeval{\PI^\PI}$ and
\$displaystyle\int\limits_1^\infty\frac{1}{x^2}\symup dx=1$
\unsetBold
```

```
\setBold\noindent% Using the default value
An example:
$\pi^\pi=\fpeval{\PI^\PI}$ and
\$displaystyle\int\limits_1^\infty\frac{1}{x^2}\symup dx=1"
\unsetBold
\end{document}
```

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$

An example: $\pi^\pi = 36.46215960720789$ and $\int_1^\infty \frac{1}{x^2} dx = 1$